



## 3232S-XL

32x32 Analog Balanced Stereo Audio Matrix Switcher

| Ethernet - RJ-45



The Lassen XL Series offers flexibility and adaptability to any application where saving space and costs are important. 3232S-XL is a 32x32 analog balanced stereo audio matrix switcher, available in a compact 3RU frame. It offers control via the front panel or remotely via RS-232 or Ethernet

### TECHNICAL SPECIFICATIONS

|              |                                                                                                                                                                                                                |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inputs       | 32 Balanced/Unbalanced Stereo Analog Audio: On 5-pin terminal block connectors                                                                                                                                 |
| Outputs      | 32 Balanced/Unbalanced Stereo Analog Audio: On 5-pin terminal block connectors                                                                                                                                 |
| Ports        | 2 Sync: On BNC connectors<br>1 Ethernet: On an RJ-45 connector<br>1 RS-232/422: On a 9-pin D-sub connector<br>2 RS-485: On male mini-XLR connectors, for control panel<br>1 AC Power: On an AC power connector |
| Analog Audio | Input - Max. Source Level +24dBu<br>Input - Impedance $>20k\Omega$<br>Output - Max. Source Level +24dBu balanced +18dBu unbalanced<br>Output - Impedance $<50\Omega$                                           |
| Enclosure    | Size: 19" — 3U — mounts in a standard 19" rack<br>Dimensions: 19" x 18.5" x 5.25" W, D, H                                                                                                                      |