

6241HDxI

4x1 3G HD-SDI Switcher

| 3G HD-SDI - BNC



The 6241HDxl is a high-performance switcher for 3G HD-SDI video signals. It takes any one of four 3G HD-SDI inputs, provides reclocking and equalization, and outputs the signal to one 3G HD-SDI output

FEATURES

Max. Data Rate - 3Gbps

HDTV Compatible

Multi-Standard Operation - SDI (SMPTE 259M and SMPTE 344M), HDSDI (SMPTE 292M) and 3G HDSDI (SMPTE 424M)

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances



TECHNICAL SPECIFICATIONS

INPUTS: 4 SMPTE 259M/344M serial digital video inputs (75) on BNC connectors

OUTPUTS: 1 SMPTE 259M/344M serial digital video output (75) on BNC connectors

MAX. DATA RATE: 2.97Gbps

MAX. OUTPUT

LEVEL:

800mVpp/75

EQUALIZATION: Automatic equalization for losses on 75 coaxial cable

POWER

CONSUMPTION:

5V DC, 410mA

INCLUDED

ACCESSORIES:

Power supply, mounting bracket

OPTIONS: RK3T 19" rack adapter

PRODUCT

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

DIMENSION:

PRODUCT WEIGHT: 0.2kg (0.5lbs) approx

SHIPPING

23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H

DIMENSION:

SHIPPING WEIGHT: 0.5kg (1.2lbs) approx

