

670T

4K UHD HDMI over Fiber Optic Transmitter

| HDMI | HDCP Compliant | 4K/60 UHD (4:2:0)



The 670T is a highperformance fiber optic transmitter for 4K UHD HDMI signals. The unit converts an HDMI signal to light pulses that it transmits over one single fiber optic cable to the 670R receiver that converts them back to a 4K UHD HDMI signal

FEATURES

Max. Resolution - Up to 4K@60Hz (4:2:0) UHD when connected to 670RN and WUXGA

Max. Data Rate - Up to 3.5Gbps

HDTV Compatible

HDCP Compliant

EDID PassThru - Passes EDID signals between the source and display

HDMI Support - Deep Color, $x.v.Color^{TM}$, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTSHD, CEC

3D Pass-Through

Signal Transmission - Transmits four TMDS video channels as well as one lowspeed channel for passing HDCP, EDID and a Hot Plug Detect (HPD) signal over one multimode fiber

Laser Standards Compliance - IEC 608251, FDA 21CFR1040; Laser Class 1: Safety of laser products System Range - 1700m (5570ft)

Cable - Multimode fiber optic OM3 cable with SC connectors

Compact DigiTOOLS® - 3 units can be rack mounted sidebyside in a 1U rack space with the optional RK3T rack adapter



TECHNICAL SPECIFICATIONS

INPUTS: HDMI connector

OUTPUTS: 1 optical connector

BANDWIDTH: Supports up to 3.5Gbps bandwidth per graphic channel for resolution 4K@60 UHD

(4:2:0), 4Kx2K

COMPLIANCE WITH

HDMI STANDARD:

Supports HDMI using fiber optic communication links and DDC2B

EXTENSION LIMIT: 1700m (>5570 feet) for 1080p/60Hz

INSERTION LOSS

FROM

TRANSMITTER TO

RECEIVER:

Must not exceed 10dB

FIBER-OPTIC CONNECTION:

SC connectors for multimode (OM3) fiber cable (not supplied with the unit)

INDICATOR LEDs: Video, source, acceptor fiber and on LEDs

POWER

CONSUMPTION:

5V DC, 250mA

PRODUCT DIMENSION:

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H $\,$

PRODUCT WEIGHT: 0.2kg (0.4lbs) approx

SHIPPING

15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

DIMENSION:

SHIPPING WEIGHT: 0.5kg (1.1lbs) approx

INCLUDED

ACCESSORIES:

Power supply, bracket installation kit

OPTIONS: HDMI/HDMI male to male cable

