



861

18G 4K HDR Pocket Signal Generator,
Analyzer and Cable Tester

| HDMI | 4K/60 UHD (4:4:4)



861 HDMI 18G (6G per graphic channel) 4K HDR Pocket Signal Generator, Analyzer and Cable Tester is an advanced and handy tool for generating, testing and verifying the signal path within your (up to) 4K@60Hz (4:4:4) HDMI 2.0/HDCP 2.2 ecosystem. With 23 built-in resolutions, 11 test patterns and over a dozen types of AV analysis functions, this unit provides an enormous range of testing options. HDMI data packet, EDID and HDCP analysis are supported along with EDID upload and emulation. Additionally, the Status and Control Data Channel (SCDC) can be monitored, enabling HDMI 18G signal detection and analysis. Up to 8 channels of LPCM audio test tones can be generated with a wide range of frequencies and audio levels.

861 is portable and durable, it includes a high-quality belt pouch and runs on a Li-Ion battery that operates for over 5 hours before needing to be recharged

FEATURES

Max. Resolution - 4K@60Hz (4:4:4)

Standards Compliance - HDR10, HDMI 2.0, DVI 1.0 and HDCP 1.4/2.2

Data Path Analysis - Source and sink up to 18G HDMI signals (6G per graphic channel)

HDMI Data Packet Analysis

HDCP v1.4 and v2.2 Analysis & Control

EDID Data Analysis & Emulation - Including SCDC

HDR Bypass & Analysis Support

HDMI Timing Generation - Up to 4096×2160 @60Hz (4:4:4), 8-bit

Supported Output Resolutions - 480p, 576p, 720p@25/30/50/60, 1080i@50/60, 1080p@24/25/30/50/60, 4K(3840×2160p)@24/25/30/50/60, 4K(4096×2160p)@24/25/30/50/60

LPCM Sinewave Audio Generation - Up to 8 channels

Cable Tester - Suitable for 4K HDMI cables. Includes tests for 5V, CEC and hotplug detection support

OLED Display - With rapid updates of current status information

Detailed OSD - For settings and informational displays

USB Firmware Update

Portable and Durable

Includes a ≥5 Hour (typical) Operating Life Li-Ion Battery

Power Saving Features



TECHNICAL SPECIFICATIONS

1 HDMI:	On a female HDMI connector
1 HDMI:	On a female HDMI connector
1 USB:	On a female Micro-B connector
Max Data Rate:	18Gbps (6Gbps per graphic channel)
Max Resolution:	4K UHD @60Hz (4:4:4, 8-bit)
Supported Output Resolutions:	480p@59Hz, 576p@50, 720p@25/30/50/60, 1080i@50/60, 1080p@24/25/30/50/60, 4K(3840×2160p)@24/25/30/50/60, 4K(4096×2160p)@24/25/30/50/60
Standards Compliance:	HDMI 2.0 and HDCP 1.4, 2.2
Audio (Embedded) Output Support:	LPCM 2.0, 5.1, and 7.1
Source:	5V, 2.1A USB Power
Consumption:	4.7W
Operating Temperature:	0° to +40°C (32° to 104°F)
Storage Temperature:	-20° to +50°C (-40° to 158°F)
Humidity:	20% to 90%, RH non-condensing
Safety:	CE, FCC
Environmental:	RoHs, WEEE
ESD Protection:	Human body model – ±12kV (Air Discharge), ±8kV (Contact Discharge)
Type:	Metal
Cooling:	Convection Ventilation
Included:	Micro-B USB cable, 1 C-HM/HM/PICO/BK-3 cable, 1 lithium-ion 3.6V/3200maH rechargeable battery, belt pouch

