



KRAMER

905xl

Stereo Audio Power Amplifier (110 Watts per Channel)

| Speakers



The 905xl is a high-performance remote-controllable power amplifier

FEATURES

Stereo Mode - 2 x 110W @4

Selectable Balanced and Unbalanced Inputs

Remote Control (RS-232) - Volume, EQ and input selection

Class D Amplifier



KRAMER

TECHNICAL SPECIFICATIONS

INPUTS:	1 unbalanced stereo audio on RCA connectors, 1 balanced stereo audio on a 5pin terminal block connector
OUTPUT:	1 speaker stereo audio on a 4pin terminal block connector
INPUT SENSITIVITY:	760mVpp (unbalanced), 1.2Vpp (balanced)
OUTPUT POWER:	55W per channel into 8, 110W per channel into 4
MAX. VOLTAGE GAIN:	8: 49dB (unbalanced), 45dB (balanced) 4: 47dB (unbalanced), 44dB (balanced)
OUTPUT MUSIC POWER:	300W per channel into 4
BANDWIDTH (–3dB):	>26kHz
S/N RATIO:	80dB
CROSSTALK:	–120dB @1kHz, –111dB @20kHz
CONTROLS:	Bass:–15dB to 14dB @100Hz; mid: –13.7dB to 13.7dB @1kHz; treble: –13.7dB to 13.8dB @10kHz; balance: –46.9dB to 0dB; volume: –80dB to 32dB @1kHz
ADDITIONAL CONTROLS:	Loudness: –9dB @500Hz, –9dB @1kHz, –8.5dB @15kHz
COUPLING:	Input: AC, Output: DC
AUDIO THD + NOISE:	<1% @1kHz, 1V
AUDIO 2nd HARMONIC:	<0.1% @1kHz
AMPLIFIER TYPE:	Class D
POWER CONSUMPTION:	220/110V AC, 50/60Hz, 510VA
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	40° to +70°C (40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
INCLUDED ACCESSORIES:	Power cord, rack "ears"
PRODUCT DIMENSION:	19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H
PRODUCT WEIGHT:	1.4kg (3.1lbs) approx
SHIPPING DIMENSION:	55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H
SHIPPING WEIGHT:	2.2kg (4.9lbs) approx

