

## System Requirements

- Microsoft Windows 8, 10
- Mac OS

## Connections:

- USB:Version 2.0 Compatible  
Type:Mini-B Female
- Keyed Connector: Keyed RJ-45 (8-conductor)

## Controls:

- Volume Up
- Volume Down
- Microphone Mute

## Audio:

- Speaker:
  - Bandwidth: 190 Hz - 20 kHz
  - Max Output Level: 85 dB SPL @ 1 foot (0.30 meter)
- Microphone:
  - Bandwidth: 50 Hz - 7.75 kHz

## Environmental:

- Operating Temperature:
  - 41 - 104° F (5 - 40° C)
- storage Temperature:
  - 32 - 158° F (0 - 70° C)

## Processing:

- Full Duplex
- Distributed Echo Cancellation (D.E.C.)®
- Noise Cancellation (NC)
- Automatic Level Control (ALC)
- Line Echo Cancellation (LEC) - Selectable
- First-Mic Priority

## Power:

- USB: 5 VDC @ 500 mA Maximum
- External:
  - Input: 100 - 240 VAC
  - Output: 9 VDC @ 560 mA
  - Tip: Power • Ring: Ground

## Mechanical:

- Dimensions (W x D x H):
  - 7.4" x 7.4" x 1.8" (18.8 cm x 18.8 cm x 4.6 cm)
- Weight:
  - 1.17 lbs (0.53 kg)

## Compliance:

- RoHS
- REACH
- FCC Class A Part 15
- CES-003
- CE Listed
- UL Listed

## Model numbers:

- 910-156-250 CHAT 170:
  - Single CHAT 170 and Connecting Cable
- 910-156-250-00 CHATAttach 170:
  - Two (2) CHAT 170 Devices, Connecting Cables and Power Supply

## Accessory Part numbers:

- 910-156-225 CHATAttach expansion Kit:
  - Includes Cables, Power Supply and Quick-Start Guide to Update Two (2) CHAT 170 Devices to CHATAttach