



www.alfatronelectronics.com

ALF-VM-41



1、Introduction	5
1.1 Brief	5
1.2 Features	5
2、Interfaces	6
2.1 Description	6
3、Configuration	7
4、Front Panel	8
4.1 Front Panel Description	8
5、Operation	9
5.1 Switching	9
5.2 Layer control	9
5.3 ON/OFF Function Keys	9
5.4 Shortcut keys	9
5.4.1 AUDIO:Audio Menu ON/OFF	9
5.4.2 EFFECT:Switching Effect menu	10
5.4.3 SCENES:AB Layout Menu	10
5.5 PTZ Control	10
5.6 Lock	10
5.7 FTB	10
5.8 Key Leds	11
6、LCD Monitor	12
7、Menu	12
7.1 Transition	12
7.1.1 Transition configuration	12
7.1.1.1 MIX	12
7.1.1.2 DIP	12
7.1.1.3 WIPE	13
7.1.2 Duration Time	13
7.1.3 FTB Time	13
7.1.4 Softness	13
7.1.5 DIP Configuration	13
7.2 Layer	13
7.2.1 Layer Source	13
7.2.2 Position/Size	14
7.2.3 Mask	14
7.2.4 Keying Configuration	14
7.2.5 Chroma	14
7.2.5.2 Region	15
7.2.5.3 Similarity	15
7.2.5.4 Smoothness	15
7.2.6 Luma Key	15
7.2.6.1 Min/Max	15
7.2.6.2 Reverse	15
7.2.6.3 Similarity	15
7.2.6.4 Smoothness	15
7.3 Audio	15
7.3.1 PGM Audio	15
7.3.2 HDMI Audio	16
7.3.2.1 Mix Mode	16
7.3.2.2 Volume	16
7.3.2.3 Audio Delay	16
7.3.3 Mic 1/Mic 2	16
7.3.3.1 Mix	16
7.3.3.2 Volume	16
7.3.3.3 Audio Delay	16
7.3.3.4 Mode	16

7.3.4 Headphone	16
7.4 Image.....	16
7.4.1 Pattern	17
7.4.1.1 Image Selection	17
7.4.1.2 Image Deletion	17
7.4.2 Add Image.....	17
7.4.3 LOGO	17
7.4.3.1 LOGO Select.....	17
7.4.3.2 LOGO Deletion.....	17
7.4.4 Add LOGO	17
7.4.5 LOGO Position.....	17
7.5 Multi Media	18
7.5.1 H.264	18
7.5.2 Stream	18
7.5.3 Record	18
7.6 Screen Monitor	18
7.6.1 LevelMeter	18
7.6.2 Input Information	18
7.6.2.1 Visible	18
7.6.2.2 Opacity.....	19
7.6.2.3 Position/Size	19
7.6.2.4 Font Color	19
7.6.2.5 Background Color.....	19
7.6.3 UMD.....	19
7.6.3.1 Visible	19
7.6.3.2 Opacity.....	19
7.6.3.3 Position/Size	19
7.6.3.4 Font Color	19
7.6.3.5 Background Color.....	19
7.7 Output.....	19
7.7.1 Mode.....	19
7.7.2 Color	19
7.8 Camera.....	20
7.8.1 Camera Select	20
7.8.2 Camera IP	20
7.8.3 Search	20
7.8.4 Focus	20
7.8.5 Exposure.....	20
7.8.6 White Balance.....	21
7.9 Setting	21
7.9.1 System Setting.....	21
7.9.1.1 Language	21
7.9.1.2 Backlight.....	21
7.9.1.3 Fan.....	21
7.9.1.4 Reset.....	21
7.9.2 Time Setting	22
7.9.2.1 Date.....	22
7.9.2.2 Time	22
7.9.2.3 Time Format.....	22
7.9.3 Network.....	22
7.9.4 Firmware.....	22
7.9.5 Help	22
8、Upper Computer.....	23
8.1 Connect the upper computer	23
8.1.2 Using PC.....	23

8.1.3 Using Phone	23
8.2 Switcher Setting	23
8.2.1 Front Panel	24
8.2.2 EFFECT	24
8.2.3 SCENES	24
8.3 Media Setting	24
8.3.1 Streaming Setting	25
8.3.1.1 Streaming Address	25
8.3.2 Picture Upload	25
8.3.3 LOGO Upload	25
8.4 Audio Setting	25
8.4.1 PGM/HP	26
8.4.2 Micphone Audio Setting	26
8.4.3 Quad HDMI Audio	26
8.5 Update	26
8.5.1 System Update	26
8.5.2 EDID Update	26
8.6 Transitions	27
8.7 Layer	27
8.7.1 Layer Position/Size	27
8.7.2 MASK	27
8.7.3 CHROMA Key	28
8.7.4 LUMA Key	28
8.8 Setting	28
8.8.1 SYSTEM Setting	28
8.8.2 TIME Setting	28
8.8.3 NETWORK Setting	28

1 Introduction

1.1 Brief

The switcher is a multi functional and professional quad HDMI video switcher with a 5.5" FHD LCD, and joystick. Users can easily monitor the sources and the PVW, conveniently control PTZ cameras. It is suitable for live broadcast and streaming.

The switcher is high performance and accelerated by FPGA, with digital video effects, chroma key, flexible PIP/PO, Logo and other functions for broadcasting. The switcher supports UVC streaming, multi network streaming and local video recording.

1.2 Features

- **5-inch full HD LCD display:**
Built-in 5-inch HD screen, Integrates live streaming and monitoring functions.
- **Support T-shaped fader switching video output control:**
Damping feel fader, supports 30 switching effects.
- **4 HDMI input video sources, 2 PGM HDMI output:**
Supports up to 4 video inputs and 1080P60 image input.
1 channel UVC video signal output.
- **Supports RTMP streaming protocol, live broadcast at any time:**
Supports RTMP streaming media protocols to implement streaming; supports stream size setting and simultaneous streaming from 2 addresses.
- **Dual HDMI outputs:**
Both channels can output PGM
- **A variety of PIP layouts and transition effects, which can be freely converted according to needs:**
Supports multiple PIP and POP layouts and multiple transition functions.
- **MP4 video recording, retains wonderful works:**
Supports MP4 format video recording and saving.
Supports USB mobile hard disk storage.
- **Convenient and fast camera control functions:**
4D joystick PTZ control; supports VISCA Over IP control protocol.
- **Powerful WEB control background:**
Supports remote control of broadcasting and parameter configuration through the WEB background, and supports WEB equipment upgrades.

2、Interfaces

2.1 Description

1	MIC/Line(3.5mm stereos) *2 (Audio input)
2	Line(3.5mm stereos) * 1 (Audio input)
3	TALLY extend port, support external TALLY box
4	USB-A (Record video with USB disk, logo/pictures import, Firmware update, USB to serial port control function (need to use converter)
5	HDMI IN x 4
6	PGM Out x 2
7	USB Type C (UVC streaming)
8	LAN (Web control and network streaming)
9	DC 12V IN (Power supply)
10	Power switch



3.Configuration

parameters	
Video Source	HDMI IN x 4
Video Output	PGM x 2 UVC x 1
Audio Input	MIC/Line level(3.5mm stereos)x2
USB	USB x 1
Lan	LAN x 1
Power	DC 7~12V ≤12W
Function	
Switching	T-Bar/AUTO/ CUT
Effects	WIPE/MIX/DIP/PAT/STILL/MUTE/FTB
Layout	Multi Layout format (see 5.4.3)
Keying	Luma Key Chroma Key
Audio Sources	HDMI x 4 and MIC/ Line level x 2;
Audio Delay	0-5s
Media	Importable pictures and logos
Video format	
HDMI Input	1080p 60/59.94/50/30/29.97/25/24/23.98 1080i50/1080i60 720p 60/59.94/50/30/29.97/25/24/23.98 576i/480i/576p/480p
HDMI PGM output	1080p 60/50/30/25/24 1080i50/1080i60
HDMI color format	RGB/YUV
USB streaming	max 1080p60
Stream media	H.264 encoder, supports video recording and 2 network streaming, with adjustable code rate
Others	
Power Supply	7~24V
Size (LWD)	(W)354* (D)165* (H)121mm (Including rocker height)
Weight	2kg
Temperature	Working: 0°C~50°C, Storage: -30°C~70°C
Accessory	Transformer (12V 2A) x1;

4. Front Panel

4.1 Front Panel Description



1	CAM1-CAM4	Camera mode, active with lighting
2	PGM KEY:1-4	PGM indicator and directly switching key. See 5.1
3	PVW KEY:1-4	PVW indicator and Layer A/B select key. See 5.1
4	Lock	Lock key, active with red blinking. It lock all the keys on front panel to avoid faulty operation.
	FTB	Force PGM to black immediately, as well as mute PGM auto immediately. Active with red blinking
	MUTE	PGM Mute, active with red blinking
5	STREAM	Active with green blinking
	REC	Active with green blinking
	AUDIO	Audio menu. See 5.4.1
	SHOT	Screen shot of PGM Signal
6	CHROMA/LUMA	When tuened on, the button light will light up
	SCENES	Scenes menu. See 5.4.3
	LOGO	LOGO key
	A/B	A/B layer select key for PVW
7	WIPE	Switching effect menu. See 5.4.2
	MIXD/P	MIXD/P effect
	SPEED	Set transition speed. See 7.1.2
8	AWB knob	Switch white balance mode and manually adjust the red and blue gain with the knob
	AE knob	Switch explosure mode, manually adjust aperature, shutter and gain with the knob
	FOCUS knob	Switch focus mode and manually adjust the focal length with the knob
9	ZOOM rocker	Controls the camera to zoom in and out
10	POS1 - POS4	Camera position record. See 5.5
11	PTZ Joystick	The joystick is multifunction and these functions are exclusive: 1. Camera control.See 5.5 2. Layer control:Layer position, PIP/POP mask position,Logo position, UMD position
12	MENU/ MENU KNOB	MENU: System menu KNOB: Multifunctional: Menu selection/Menu enter/Layer size control

	Setting the PT speed of camera
STILL	PGM freezing
PAT	Pattern selection in PVW
CUT/AUTO	Switch PVW and PGM directly and immediately AUTO Switch PVW and PGM automatically with preset effect
T-Bar	Manually switch with T-Bar

5、Operation

5.1 Switching

Switching can be controlled by PVW, PGM, CUT, AUTO, PAT Keys and T-Bar.

PAT Pattern select for current layer in PVW

PVW KEY 1-4 : Source select for current layer in PVW

PGM KEY 1~4 : Source select for directly switch in PGM. When there are two layers in PGM the selected source will display as Layer B

CUT: Switch PVW and PGM directly and immediately AUTO:

Switch PVW and PGM automatically with preset effect T-Bar:

Switch PVW and PGM manually with preset effect

5.2 Layer control

Both PGM and PVW support up to two layers, Layer A and Layer B. Each layer can be separately configured, including source, size, position, mask and keying.

A KEY/B KEY: Layer A/B control

If A/B KEY isn't active, Layer A/B doesn't display in PVW and A/B KEY is pressed, the A/B KEY will be active and Layer A/B will display in PVW.

If A/B KEY isn't active, Layer A/B already displays in PVW and A/B KEY is pressed, the A/B KEY will be active and Layer A/B will display on the top layer in PVW.

If A/B KEY is active, and A/B KEY is pressed, the A/B KEY will be inactive and Layer A/B will be removed in PVW.

Note: PVW needs at least one layer. Therefore, if Layer A is inactive, B key will active and Layer B will display in PVW, and vice versa. If there is only one layer in PVW, the corresponding Key will be active and it will keep active even being pressed.

Five Way Rocker :When Five Way Rocker is idle, user can use it to move the selected layer

Menu Knob : When Menu Knob is idle, user can use it to adjust the size of the selected layer

5.3 ON/OFF Function Keys

LOGO : Set LOGO ON/OFF

CHROMA: Set chroma keying of the selected layer ON/OFF

LUMA: Set luma keying of the selected layer ON/OFF REC:

Set video record ON/OFF

STREAM: Set streaming ON/OFF STILL:

Set freezing PGM ON/OFF

5.4 Shortcut keys


5.4.1 AUDIO: Audio Menu ON/OFF

User can evoke audio menu by pressing AUDIO key. In the Menu, user can:

1. Select audio channel with Five Way Rocker

2. Adjust volume of the selected audio channel with Menu Knob

3. Set ON/OFF of the selected audio channel by pressing Menu Knob




5.4.2 EFFECT : Switching Effect menu

User can evoke Switching Effect Menu by pressing EFFECT key. In the Menu, user can select preset switching type and style. And the Auto and T-BAR switching will implement the selected preset.



5.4.3 SCENES : AB Layout Menu

User can evoke AB Layout Menu by pressing SCENES key. In the Menu, user can select preset layout. And AB layers will display as preset.



5.5 PTZ Control

When there is at least one camera, and the connection is fine, the user can control the camera with CAM, POS and Five Way Rocker, PGM Keys, PVW Keys. The operations are:

1. Activate the camera: Press CAM Key. The PTZ Control Mode will be active. And the CAM light keep blinking.
2. Camera Control: Use PVW Keys 1-4 to control Camera 1-4. When the user presses a PVW Key, the key will keep blinking and the corresponding camera is active. The left/right/up/down motion is controlled by the Five Way Rocker. And the Zoom In/Out is controlled by the Menu Knob. Therefore, the user can use both hands to implement camera motion and zoom at the same time.
3. Camera Position Record and Recall: When the user complete adjusting the camera and finding the view, the user can save the camera position and agilely evoke the camera moving to the saved position, without additional adjusting and finding.
4. Position Record: After activate the camera, press POS Key, then press PGM Key 1-4 to save the corresponding camera position.

Position Recall: After activate the camera, press the corresponding PGM Key to recall the saved position. The camera will automatically move to the position.

5.6 Lock

Long press the Lock Key for more than 2 seconds, and activate the Lock function with lock light blinking. When Lock is active, pressing any keys will not take effect. The Lock can keep the working status and prevent from faulty operation.

Long press again will inactivate the Lock function.


5.7 FTB

When pressing FTB, the PGM will be forced to black, and the volume of PGM will forced to mute.

5.8 Key Leds

Key Leds	OFF	ON	Blinking
LOCK	OFF	-	Locking
MUTE	OFF	-	PGM MUTE
LOGO	OFF	Logo On	-
AUDIO	Audio Menu Off	Audio Menu On	-
EFFECT	Effect Menu Off	Effect Menu On	-
SCENES	Scenes Menu Off	Scenes Menu On	-
A	Layer A unselected	Layer A selected	-
B	Layer B unselected	Layer B selected	-
CHROMA	Chroma Key Off	Chroma Key On	-
LUMA	Luma Key Off	Luma Key On	-
REC	Off	-	Recording
STREAM	Off	-	Streaming
CAM	Off	-	Camera Activated
POS		Waiting Pressing PGM Key 1-4 to recall camera position	-
PGM1~4	Source unselected	Source selected	-
PVW1~4	Source unselected	Source selected	-
STILL	Off	-	PGM Freezing
PAT	Off	Activate pattern as source	-
AUTO	Off	Automatically switching	-
FTB	Off	-	PGM force to black and mute

6、LCD Monitor




①	LOGO	⑦	Date&Time	⑬	MIC1 Vol Meter
②	PAT	⑧	Recording Status	⑩	MIC2 Vol Meter
③	EFFECT	⑨	Streaming Status	⑮	PGM Vol Meter
④	TRANS Time	⑩	U-Disk Status	⑩	UMD
⑤	CAMERA Info	④	Signal Status	④	System
⑥	ENCODER Info	⑫	HDMI IN Vol Meter		

7. Menu


7.1 Transition

There are transitions including WIPE, MIX, DIP. The user can trigger a transition by pressing AUTO, or manually control the transition with T-BAR.

The user can enter the transition menu by pressing Menu Key or rotating the Menu Knob then selecting  in the main menu.

7.1.1 Transition configuration

In the transition Menu, the user can select from MIX, DIP, WIPE, including more than 30 styles.



7.1.1.1 MIX

Select MIX in the transition menu, configure the transition time. Then the user can auto trigger or manually control the MIX transition.

7.1.1.2 DIP

Select DIP in the transition menu, configure the transition time. In the DIP menu, two styles can be select. One is DIP with color, and the default color is black. The other is DIP with background, which can be set in the library.

7.1.1.3 WIPE

Select WIPE in the transition menu, configure the transition time. In the WIPE mode, there are plenty styles to be selected, including horizontal, vertical, corner, cross, circle, diagonal, etc. The user can also configure the smoothness. The smoothness can make the edge smoother.

7.1.2 Duration Time

In the transition menu, the user can set the duration time. Larger value of time means the transition will last a longer time, and vice versa. The time range could be 0.1s-5.0s and the default is 0.5s



7.1.3 FTB Time

In the FTB Time menu, the user can set the time from pressing the FTB Key to forcing PGM black.




7.1.4 Softness

Select Transition Menu and select softness, turn the Menu Knob to change the softness. Smaller value means sharper edge, and greater value means smoother edge. The range is 0-100 and the default value is 20.



7.1.5 DIP Configuration

Select Dip to set Mode and Color. When select Color as Mode, the user can set the dip color. When select Image, the dip will work with the preset background picture.



7.2 Layer

The switcher supports A/B layers. So, it can implement PIP/POP. And the size and position can be set as the user need.

Click Menu and enter the menu, select



7.2.1 Layer Source

In the Layer menu, the user can select the layer source by turning the Menu Knob. The user can select PVW 1-4 or PAT as the Layer source.




7.2.2 Position/Size

In the Layer menu, the layer size can be set by the Menu Knob, and the position can be set by the five-way rocker. The position and the size information also display in the menu.



7.2.3 Mask

In the Layer menu, the user can set the layer mask Select Mask and turn it on. Then set the size and position.



7.2.4 Keying Configuration

The user can create lifelike virtual studio with Keying functions in the switcher. The keying function can work on multi stream and achieve very good keying result, including clean keying, detail retaining and edge balance, to meet the need of the users.



7.2.5 Chroma

Chroma Key is commonly used for virtual studio, such as weather broadcasts, news broadcast, film, gaming and so on. In the studio the presenter is actually standing in front of a green or blue background. In chroma key two images are combined using a special technique and the background color of one image is removed. Then the remaining foreground displays over another image.

In the Layer Menu, select chroma key, set the key color, the similarity and smoothness.



When press CHROMA KEY, it firstly works in PVW, and the CHROMA KEY will light green.


7.2.5.1 Color

In Chroma Key menu, the user can set the HVS value of the key color.



7.2.5.2 Region

In Chroma Key menu, select Region, there is a rectangle in the top layer of A/B. The size of the rectangle can be set by turning the menu key, and the position can be adjusted with the five-way rocker.



7.2.5.3 Similarity

In chroma key, the Similarity adjusts the color range from the set key color. The greater value means wide key range. The default is 0.

7.2.5.4 Smoothness

In chroma key, the Smoothness can help to remove the background very closed to the edge of the foreground. It's useful to get clear edge of the foreground, without any annoying artifacts visible. The greater value of smoothness means more clear and smoother edge. The default is 0.

7.2.6 Luma Key

The luma key using luma value to get a luma matte of the foreground video, which removes away the black background of the foreground video. And the remaining will display over another background video.

In the Layer Menu, select luma key, set the min, max, reverse, the similarity and smoothness.

When press LUMA KEY, it firstly works in PVW, and the LUMA KEY will light green.



7.2.6.1 Min/Max

The Min/Max adjust the range of luma key. And the luma value of the foreground video, out of the range, will be keyed away. The range is 16-235 and the default is 16.

7.2.6.2 Reverse

The Reverse keys away the luma value out of the range from min to max.

7.2.6.3 Similarity


In luma key, the Similarity adjusts the color range from the set key luma. The greater value means wide key range. The default is 0.

7.2.6.4 Smoothness

In luma key, the Smoothness can help to get smoother edge. The default is 0.


7.3 Audio

Support audios from 4 HDMI sources and 2 3.5mm mic sources. Each source has separate enable, volume, mix, delay control. The HDMI sources can be AFV.

Pressing Menu Key, in the menu select 

7.3.1 PGM Audio

In the PGM, the Mute will turn off the audio in the PGM. The Volume range is -60dB to 0dB. The default is -5dB.



7.3.2 HDMI Audio

In the Audio Menu, there are 4 HDMI sources that can be set.

7.3.2.1 Mix Mode

The mix mode can be Off/On/AFV.

When set as AFV, the source audio will be active only when the video also displays in PGM.



7.3.2.2 Volume

The volume of each source can be adjusted separately. The range is -60dB to 0dB. The default is -5dB.

7.3.2.3 Audio Delay

The audio delay of each source can be set separately. Adjust the delay and keep the synchronization between the audio and the video. The max delay is 5 secs. The default is 0 sec.

7.3.3 Mic 1/Mic 2

In Audio Menu, Mic1/Mic2 can be set. The Mic source can be linear audio device, desktop audio, lapel microphone and so on.

7.3.3.1 Mix

User can turn on or off the mixer. The default is on.



7.3.3.2 Volume


The volume of each source can be adjusted separately. The range is -60dB to 0dB. The default is -5dB.

7.3.3.3 Audio Delay

The audio delay of each source can be set separately. The max delay is 5 secs. The default is 0 sec.

7.3.3.4 Mode

There are mic and line mode for Mic 1/Mic 2. When the source device is microphone, set the mic mode. When the source device is line device, set the line mode.




7.3.4 Headphone

There is a headphone output in the switcher. User can monitor the audios by the headphone. The source of the headphone can be PGM audio, any source of HDMI and Mics. The default source is PGM audio. The volume of headphone can be adjusted, and the range is -60dB to 0dB. The default is 0dB.


7.4 Image

In the Image, the pattern, logo can be set.

Pressing MENU, select 

7.4.1 Pattern

In the Image, select Image to show the pictures.



7.4.1.1 Image Selection

Select the image by turning the Menu Knob, then press the Knob. Select IMG1 at the bottom and press the Knob. The image is set as default background Pattern.



7.4.1.2 Image Deletion

The operation is similar to Image Selection. The difference is select DEL in the bottom.

7.4.2 Add Image

Images can be import from U-Disk. Insert U-Disk and there will be a USB icon at the bottom. Please make sure the images are saved in the “images” directory. Then select the images and import to the switcher. **PS: The max size supported is 1920x1080.**

7.4.3 LOGO



7.4.3.1 LOGO Select

In Logo configuration, select LOGO and load preset LOGO.


7.4.3.2 LOGO Deletion

Select the preset LOGO with the Menu Knob, then press the knob. Select DEL at the bottom of the menu and delete the LOGO.

7.4.4 Add LOGO


Save LOGOs in the “logos” directory in the usb -disk, insert the usb-disk and there will be a USB icon at the bottom of the status/menu page. Then add the logos from the logo add menu.

The size of the logos should not be larger than 960x540. And formats such as *.png, *.jpeg, *.jpg, *.bmp are supported.




7.4.5 LOGO Position

In logo position, adjust the position of logo with the five away rocker.




7.5 Multi Media

In the multimedia, users can check and adjust the encoder, network streaming, recording.

Press MENU and then select 


7.5.1 Encoder

In encoder, there are framer rate and code rate can be adjusted. The range of frame rate is 10-60, the range of code rate is 1mbps-30mbps. The default frame rate is 60, and the code rate is 5mbps.



7.5.2 Stream

In Multimedia Settings, select Stream. Two streaming addresses can be saved in network streaming. Click STREAM to start streaming. If the streaming address is available, the STREAM button flashes green and starts streaming, and the streaming address is displayed in green. If the streaming address is abnormal, the streaming address is displayed in red and the STREAM button is off. (Note: if the output is set to i mode, streaming is not allowed)



The streaming address is configured through the Web host computer. See 8.3.1 Streaming Settings.

7.5.3 Record

The switcher records the picture and sound of PGM into the "video_rec" folder on the USB flash drive.

Support the USB flash disk format of FAT32 and NTFS (FAT32 can record 4G video at most)

When a USB key is inserted, a USB icon will appear at the bottom of the status/menu page. In Multimedia Settings, select Record to display the used capacity and available capacity of the USB flash drive. Click the REC button to start recording. The file name of the recorded file will appear below the pie chart, and the REC light will flash. Press REC again to stop recording.



Note: The system will automatically stop recording when the capacity of the USB flash disk is insufficient;

The recording will stop automatically when the FAT32 USB flash disk is 4G in size;

When the recording is not stopped normally (for example, the recording power is interrupted, and the USB stick is unplugged), the recording file cannot be used normally.

7.6 Screen Monitor

In the screen monitoring, you can operate the audio meters, input information and UMD.

Press Menu and select 


7.6.1 Level Meter

Enter the screen monitoring settings and select the level meter. The level meter of four HDMI, two MIC and PGM can be turned off and turned on at the same time, or can be set separately.



7.6.2 Input Information

Enter the screen monitoring setting, select the input info, and you can set the information of the four HDMI input signals to turn on and off, font color, etc.



7.6.2.1 Visible

Turn on the Visible and display the information of four HDMI input signals. Otherwise, turn off the Visible, and close the information.

7.6.2.2 Opacity

Opacity sets the opacity of the background of the four HDMI input information display, ranging from 0% to 100%.

7.6.2.3 Position/Size

Enter the screen monitoring setting, select the input information - position/size, control the size of resolution display through the knob, and control the display position of resolution through the PTZ rocker.

7.6.2.4 Font Color

Enter the screen monitoring settings, and select the input information font color to customize the font color of the input information.

7.6.2.5 Background Color

Enter the screen monitoring settings, select Input Information - Background Color to customize the background color of the input information.

7.6.3 UMD

Enter the screen monitoring settings, select UMD, and you can set the opening/closing, font color, etc. of UMD in PVW and PGM windows.

7.6.3.1 Visible

Turn on the Visible and display the information of PVW and PGM. Otherwise, turn off the Visible, and close the information.

7.6.3.2 Opacity

Opacity sets the opacity of the background of the UMD, ranging from 0% to 100%.

7.6.3.3 Position/Size

Enter the screen monitoring setting, select the UMD - position/size, control the size of resolution display through the knob, and control the display position of resolution through the PTZ rocker.

7.6.3.4 Font Color

Enter the screen monitoring settings, and select the UMD font color to customize the font color of UMD.


7.6.3.5 Background Color

Enter the screen monitoring settings, select UMD - Background Color to customize the background color of the UMD.



7.7 Output

In the menu, the output format and color can be set.

Press MENU and select 

7.7.1 Mode

Enter the output setting and select the mode. You can select different output modes through the knob. The default is 1080p60.



7.7.2 Color

Enter the output setting and select the color. You can select different color modes through the knob. The default is RGB Full.



7.8 Camera

The switcher supports VISCA camera control protocol. The rocker and knob can be used to quickly and conveniently control camera movement. At the same time, camera focusing, exposure, white balance and other parameters can be set in the camera menu.

In addition, it also supports the camera position storage function, which can be quickly recalled (see "5.5 PTZ Control").

Press MENU and select




7.8.1 Camera Select

Enter the camera settings, select the camera, and use the knob to select the camera to be set.




7.8.2 Camera IP

Enter the camera settings, select the camera IP, and the IP address of the camera is displayed. You can manually set the IP address.



7.8.3 Search

Enter Camera Settings, select Search, and all found camera IPs in the same LAN will be displayed. Select the camera IP through the knob.



7.8.4 Focus

Enter the camera settings and select Focus. You can set auto focus and manual focus. Manual focus can be set through the knob.




7.8.5 Exposure

Enter the camera settings and select exposure to set automatic exposure and manual exposure. Manual exposure can be set through the knob.




7.8.6 White Balance

Enter the camera settings, select white balance, and you can set automatic and manual gain. For manual, you can set the red gain and blue gain through the knob. The gain range is 0-255.



7.9 Setting

Press menu, then select 

7.9.1 System setting

Select system settings to set the system of the switch station, including the settings of language, backlight, fan and reset


7.9.1.1 Language

Enter the system settings, select the language, and select the language with the knob. The default is English.



7.9.1.2 Backlight

Enter the system settings, select the backlight, and adjust the screen backlight through the knob. The range 10% - 100%. The larger than value, the brighter the screen.




7.9.1.3 Fan

Enter the system settings, select the fan, and select the fan mode through the knob. The default is automatic mode.

Automatic mode: the fan speed is controlled according to the working temperature. The higher the temperature, the faster the speed.


Off mode: turn off the fan and switch to automatic mode only when a certain temperature is reached.

On mode: the fan is always on.




7.9.1.4 Reset

Enter the system settings, select Reset, select On through the knob, and the switch station will perform reset operation. After reset, all configurations will be cleared.



7.9.2 Time Setting

Enter the time setting to operate the time, date, countdown, etc.



7.9.2.1 Date

Enter the time setting, select the date, and set the date manually.

7.9.2.2 Time

Enter the time setting, select the time, and set the time manually.

7.9.2.3 Time Format


Enter the time setting, select the format, and the time can be set to display in 12h/24h format on the status page.

7.9.3 Network

In Network Settings, you can select to automatically obtain the network IP or manually set it.

7.9.4 Firmware

Enter the firmware settings and scan the QR code to display the ID number and Version number.



7.9.5 Help

Enter the download settings, scan the QR code to enter the download link.




8、Upper Computer

8.1 Connect the upper computer

8.1.2 Using PC

Confirm that the computer and the switcher are connected to the same LAN by automatically obtaining or manually setting the network IP address of the switcher. Open the browser on the computer side, enter the IP address of the switcher and press Enter to connect, and enter the home page of the upper computer, namely the switch page.




8.1.3 Using Phone

Ensure that the mobile phone and the switcher are on the same LAN. In the mobile browser, enter the IP address of the switcher and open it to connect to the upper computer.


8.2 Switcher Setting

Enter the switch station setting page of the upper computer to control the switch station.



8.2.1 Front Panel

The front panel of the switching table contains buttons and push rods. Click the button to control the corresponding button on the switch table and set the transition time; Push the push rod to execute the push rod transition operation.




8.2.2 EFFECT

Enter the setting page of the upper computer, click the transition effect in the EFFECT on the right to select the corresponding transition effect.




8.2.3 SCENES

Enter the switch station setting page of the upper computer, click SCENES on the right to select different scenes layouts.



8.3 Media Setting

Click the media module on the upper computer page to enter the media setting page, where you can set streaming, upload pictures, and upload LOGOs.



8.3.1 Streaming Setting

8.3.1.1 Streaming Address

Custom streaming address:

Enter the media settings page, enter the streaming server address and streaming secret key (for streaming of live broadcast platforms such as Station B and Tiger Teeth) in Streaming Address-1 and Streaming Address-2, and click Save to save the streaming address to the switcher Settings Multimedia Network Streaming; Click the push stream button to push the stream.

Default streaming:

Enter the media settings page, select the default streaming address - 1 (for local LAN streaming), and click the Save button to save the local streaming address to the address 1 in the switcher - Settings - Multimedia - Network Streaming; Click the push stream button to push the local stream.

8.3.2 Picture Upload

Enter the media settings page, in the picture upload box, click to Pick picture, select the picture to upload, and click the Upload button to upload the picture to the switcher and automatically set it as a background picture.

8.3.3 LOGO Upload

Enter the media setting page, in the LOGO upload box, click to pick picture, select the LOGO picture to upload, and click the Upload button to upload this LOGO picture to the switcher, and automatically set it as the current LOGO.

8.4 Audio Setting

Click the audio module on the upper computer page to enter the audio setting page to set the audio for PGM, headset (HP), four input (IN1-4), and two microphones (Mic1-2).

8.4.1 PGM/HP

Enter the audio setting page to set PGM mute and PGM volume; HP source selection, HP volume settings.



8.4.2 Microphone Audio Setting

Enter the audio setting page to set Mic1/Mic2 mixing, volume, delay and mode.




8.4.3 Quad HDMI Audio

Enter the audio setting page to set IN1-4 (4-way HDMI input) mixing, volume setting and delay setting.




8.5 Update

Click Update on the upper computer page to enter the Update setting page, where you can Update the operating system and EDID.




8.5.1 System Update

On the update page, click the File button in the system update, select the file to update, and click Update to perform the update operation.




8.5.2 EDID Update

On the update page, click the File button in the EDID update, select the file to update, and click update to perform the update operation.



8.6 Transitions

Enter the upper computer page, click TRANSITIONS on the left to set the transition, including the transition duration setting (Speed), black field duration setting (FTB Speed), flexibility setting (Softness), immersion color setting (Color), and immersion mode setting (DIP Mode).




8.7 Layer

Enter the upper computer page, click LAYER on the left to set the layer, including layer position/size setting (POS/SIZE), mask setting (MASK), chroma key setting (CHROMA), and brightness key setting (LUMA).


8.7.1 Layer Position/Size

Enter the upper computer page, click LAYER on the left, enter POS/SIZE, select A/B layer, press and hold the left mouse button in the box to move, and then set the layer position; Press and drag the left mouse button at the four corners to set the layer size.




8.7.2 MASK

Enter the upper computer page, click LAYER on the left, click MASK, select the mask icon, mask the horizontal position and vertical position, and pull down to select the size of the mask.




8.7.3 CHROMA Key

Enter the upper computer page, click LAYER on the left, and click CHROMA to set the color, similarity, and smoothness.



8.7.4 LUMA Key

Enter the upper computer page, click LAYER on the left, and click LUMA to set the minimum brightness, maximum brightness, inversion, similarity, and smoothness.




8.8 Setting

Enter the upper computer page and click SETTING on the left to set the system, time and network.


8.8.1 SYSTEM Setting

Enter the upper computer page, click SETTING on the left to enter SYSTEM, where you can set backlight and fan, and click ResetALL to reset.




8.8.2 TIME Setting

Enter the upper computer page, click SETTING on the left, and click TIME to set the time format (FORMAT). The date and time are obtained from the computer system by default.



8.8.3 NETWORK Setting

Enter the upper computer page, click SETTING on the left, and click NETWORK to set the network. Open DHCP to automatically obtain the network IP; Close DHCP, enter IP, subnet mask and gateway, and click Modify to manually set the network.



1. Limited warranty

1.1 This limited warranty covers defects in materials and workmanship in this product.

1.2 Should warranty service be required, proof of purchase must be presented to the Company. The serial number on the product must be clearly visible and not have been tampered with in any way whatsoever.

1.3 This limited warranty does not cover any damage, deterioration or malfunction resulting from any alteration, modification, improper or unreasonable use or maintenance, misuse, abuse, accident, neglect, exposure to excess moisture, fire, improper packing, and shipping (such claims must be presented to the carrier), lightning, power surges, or other acts of nature. This limited warranty does not cover any damage, deterioration or malfunction resulting from the installation or removal of this product from any installation, any unauthorized tampering with this product, any repairs attempted by anyone unauthorized by the Company to make such repairs, or any other cause which does not relate directly to a defect in materials and/or workmanship of this product. This limited warranty does not cover equipment enclosures, cables or accessories used in conjunction with this product.

This limited warranty does not cover the cost of normal maintenance. Failure of the product due to insufficient or improper maintenance is not covered.

1.4 The Company does not warrant that the product covered hereby, including, without limitation, the technology and/or integrated circuit(s) included in the product, will not become obsolete or that such items are or will remain compatible with any other product or technology with which the product may be used.

1.5 Only the original purchaser of this product is covered under this limited warranty. This limited warranty is not transferable to subsequent purchasers or owners of this product.

1.6 Unless otherwise specified, the goods are warranted in accordance with the manufacturer's product specific warranties against any defect attributable to faulty workmanship or materials, fair wear and tear being excluded.

1.7 This limited warranty only covers the cost of faulty goods and does not include the cost of labour and travel to return the goods to the Company's premises.

1.8 In the event of any improper maintenance, repair or service being carried out by any third persons during the warranty period without the Company's written authorization, the limited warranty shall be void.

1.9 A 7 (seven) year limited warranty is given on the aforesaid product where used correctly according to the Company's instructions, and only with the use of the Company's components.

1.10 The Company will, at its sole option, provide one of the following three remedies to whatever extent it shall deem necessary to satisfy a proper claim under this limited warranty:

1.10.1 Elect to repair or facilitate the repair of any defective parts within a reasonable period of time, free of any charge for the necessary parts and labour to complete the repair and restore this product to its proper operating condition.; or

1.10.2 Replace this product with a direct replacement or with a similar product deemed by the Company to perform substantially the same function as the original product; or

1.10.3 Issue a refund of the original purchase price less depreciation to be determined based on the age of the product at the time remedy is sought under this limited warranty.

1.11 The Company is not obligated to provide the Customer with a substitute unit during the limited warranty period or at any time thereafter.

1.12 If this product is returned to the Company this product must be insured during shipment, with the insurance and shipping charges prepaid by the Customer. If this product is returned uninsured, the Customer assumes all risks of loss or damage during shipment. The Company will not be responsible for any costs related to the removal or reinstallation of this product from or to any installation. The Company will not be responsible for any costs related to any setting up this product, any adjustment of user controls or any programming required for a specific installation of this product.

1.13 Please be aware that the Company's products and components have not been tested with competitor's products and therefore the Company cannot warrant products and/or components used in conjunction with competitor's products.

1.14 The appropriateness of the goods for the purpose intended is only warranted to the extent that the goods are used in accordance with the Company's installation, classification, and usage instructions.

1.15 Any claim by the Customer which is based on any defect in the quality or condition of the goods or their failure to correspond with specification shall be notified in writing to the Company within 7 days of delivery or, where the defect or failure was not apparent on reasonable inspection by the Customer, within a reasonable time after discovery of the defect or failure, but, in any event, within 6 months of delivery.

1.16 If delivery is not refused, and the Customer does not notify the Company accordingly, the Customer may not reject the goods and the Company shall have no liability and the Customer shall pay the price as if the goods had been delivered in accordance with the Agreement.

1.17 THE MAXIMUM LIABILITY OF THE COMPANY UNDER THIS LIMITED WARRANTY SHALL NOT EXCEED THE ACTUAL PURCHASE PRICE PAID FOR THE PRODUCT.