



Introduction

The Atлона AT-HDR-EX-100CEA-RX is a HDBaseT™ receiver for 4K and high dynamic range (HDR) content. It supports extension of 4K/UHD video @ 60 Hz with 4:4:4 chroma sampling plus HDR data, multi-channel audio, Ethernet, control signals, and power up to 330 ft. (100 m) over Category 6/6A cable. The HDR-EX-100CEA-RX is ideal for use with the AT-HDR-CAT-4ED distribution amplifier for passing 4K HDR signals to a display. A compact enclosure and remote power supplied by the transmitter means the receiver can be conveniently mounted in furniture, behind a display, or above a projector.

Key Features

- HDBaseT receiver for use with the AT-HDR-CAT-4ED distribution amplifier
- 4K/UHD capability @ 60 Hz with 4:4:4 chroma sampling
- Supports HDR10, HLG, and Dolby® Vision™ HDR formats
- Features visually lossless compression with no latency to enable HDR and 4K/60 4:4:4 video signal extension over HDBaseT
- HDBaseT input receives HDMI®, Ethernet, control signals, and power up to 330 feet (100 meters) for both 4K HDR and 1080p with Category 6/6A
- Extends bidirectional Ethernet data as well as RS-232 and IR control signals over HDBaseT
- Remotely powered by the AT-HDR-CAT-4ED over HDBaseT
- Compliant with HDCP 2.2, the latest specification for passing protected content between devices
- Multi-channel audio pass-through
- Front panel Power and Link status LEDs
- Front panel USB port for firmware updates
- Rear panel connections simplify wire management and save installation time
- Compact enclosure can be mounted in furniture, behind a display, or above a projector

Specifications

Video		
Signal	Input - HDBaseT Output - HDMI	
Copy Protection	HDCP 2.2	
Pixel Clock	600MHz	
UHD/HD/SD	4096x2160@60/50/30/25/24Hz 3840x2160@60/50/30/25/24Hz 1920x1080p@60/59.9/50/30/29.97/25/ 24/23.98Hz 1920x1080i@30/29.97/25Hz	720p@60/59.94/50Hz 576p@50Hz 576i@25Hz 480p@60/59.96Hz 480i@30Hz
VESA All resolutions are 60Hz	2560x2048 2560x1600 2048x1536 1920x1200 1680x1050 1600x1200 1600x900 1440x900 1400x1050	1366x768 1360x768 1280x1024 1280x800 1280x768 1152x768 1024x768 800x600 640x480
Color Space	YUV, RGB	
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0	
Color Depth	8-bit, 10-bit, 12-bit	
HDR	4K HDR10 and Hybrid-Log Gamma (HLG) @ 60 Hz, Dolby® Vision™ @ 30 Hz	

Audio			
HDMI Pass-Through Formats	PCM 2.0 LPCM 5.1 LPCM 7.1	Dolby® Digital Dolby Digital Plus™ Dolby TrueHD Dolby Atmos®	DTS® Digital Surround™ DTS-HD Master Audio™ DTS:X®
Bit Depth	Up to 24 bits		
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz		

Control	
RS-232	Pass through, up to 115200 baud
IR	Pass through, 30kHz to 60kHz
CEC	Pass through

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
HDMI OUT	15	5	30	10
CAT5e	295	90	330	100
CAT6/6a/7	330	100	330	100

Buttons and Indicators	
Indicators: POWER LINK	1 x LED, green 1 x LED, yellow

Connectors	
HDMI OUT	1 x Type A, 19-pin female
HDBaseT IN	1 x RJ45
OPTICAL IN	1 x TOSLINK™
RS-232 / IR	1 x 6-pin captive screw
UTILITY	1 x Mini-USB
LAN	1 x RJ45

Environmental	Fahrenheit	Celsius
Operating Temperature	+32 to +122	0 to +50
Storage Temperature	-4 to +140	-20 to +60
Operating Humidity (RH)	20% to 90%, non-condensing	

Power	
Consumption	10.4 W
BTU/h	35.5
PoE	Powered by compatible 48V transmitters

Dimensions (H x W x D)	Inches	Millimeters
Device	1.02 x 5.74 x 3.81	26 x 146 x 97

Weight	Pounds	Kilograms
Device	0.873	0.396

Certification	
Device	CE, FCC

Compliance	
NDAA-899	Yes

Warranty	
Device	10 years

Copyright, Trademark, and Registration

© 2023 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).