



HDMI 4x4 True Matrix Switcher Splitter with Control

Comprehensive's CSW-HD442-4K60 high performance HDMI Matrix with 4 HDMI inputs and 4 HDMI outputs.

It allows any four sources to be shown on the any of the four displays simultaneously, and supports 4Kx2K@60Hz (YCbCr 4:2:0). It supports reception of any audio data conforming to the HDMI specification, such as PCM, at up to 192kHz compressed audio (IEC 61937), DSD, DST, DTS, HBR and four channel ARC control. Can be operated easily through on-panel buttons, IR remote controller, RS-232 or IP control.



Features

- Switches any 4 HDMI inputs to any 4 HDMI outputs
- Supports HDCP 2.2
- Supports resolutions up to 4Kx2K@60Hz (YCbCr 4:2:0)
- Each display's inputs can be switched with the IR remote control, through RS232, or over IP
- Supports reception of any audio data conforming to the HDMI specification such as PCM at up to 192kHz, compressed audio (IEC 61937), DSD, DST, DTS and HBR.
- Supports four channel ARC control
- 2 Year Warranty

Specifications

Video Bandwidth:300MHz/3Gbps

Output Resolution: 4k2k@30Hz with 24bit RGB/YcbCR 4:4:4/YCBCR 4:2:2,and up to 4k2k@60Hz with 12bit YCBCR 4:2:0

Deep Color support 48/36/30/24-bit

Input Ports: 4x HDMI female

Output Ports: 4x HDMI female

Power Supply: DC 12V 2.5A CE/FCC/UL Certified

ESD Protection: ± 8kV (air-gap discharge) Human Body Model: ± 4kV (contact discharge)

Dimensions: 17.5" (440mm)(W) X 4.4" (110mm) (D) X 1.75" (45mm) (H)

Weight: 2.5 lbs.

Power Consumption (Max): 12W

Warranty: 2 Years

CSW-HD442-4K60 - HDMI 4x4 True Matrix Switcher Splitter with Control