

FC-24ETH

4-Port Ethernet Controller









The FC-24ETH is a bidirectional RS-232 or RS-485 to Ethernet control signal converter. It allows four RS-232 (or one RS-485 and three RS-232) controllable devices to be controlled via an Ethernet or LAN connection.

FEATURES

- Ports 3 RS-232 and 1 serial (RS-232 or RS-485 selectable), 1 Ethernet.
- Simultaneous Communication With up to 40 PC clients.
- USB Port For firmware upgrades.
- Compact MegaTOOLS™ 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-T2B universal rack adapter.

TECHNICAL SPECIFICATIONS

PORTS: 3 RS-232 and 1 serial (RS-232/RS-485 selectable) on 3-pin terminal block connectors, 1

Ethernet on an RJ-45 connector.

CONTROLS: Serial Select button, RS-485 terminator switch, DHCP and Factory Default buttons.

INDICATORS: Power, Ethernet, Serial 1, Serial I/O, and DHCP status LEDs.

POWER CONSUMPTION: 5V DC, 200mA.

OPERATING 0° to +40°C (32° to 104°F).

TEMPERATURE:

STORAGE -40° to +70°C (-40° to 158°F).

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing.

DIMENSIONS: 18.8cm x 11.3cm x 2.5cm (7.4" x 4.5" x 1") W, D, H.

WEIGHT: 0.72kg (1.59lbs) approx.

ACCESSORIES Power supply.

OPTIONS: RK-T2B 19" rack adapter.

