

FC-32

DVI to Computer Graphics/Component/HDTV Video Format Converter









The FC-32 is a high-performance format converter for DVI-D signals. The unit converts (without scaling) a DVI-D input to a computer graphics or component video output on a 15-pin HD connector.

FEATURES

- HDTV Compatible.
- Max. Resolution WUXGA & 1080p.
- Computer Graphics Video or Component (HDTV) Selector Switch.
- Compact DigiTOOLS® 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUT: 1 DVI-D, 1.2Vpp on a Molex 24-pin (F) connector, DDC signal 5Vpp (TTL).

OUTPUT: 1 VGA or YPbPr on a 15-pin HD (F) connector; YPbPr is with bi-level sync.

RESOLUTION: Up to WUXGA, 1080p.

CONTROL: Switch for RGB/YPbPr selection.

POWER CONSUMPTION: 5V DC, 570mA.

OPERATING TEMPERATURE: 0° to +40°C (32° to 104°F).

STORAGE TEMPERATURE: -40° to +70°C (-40° to 158°F).

HUMIDITY: 10% to 90%, RHL non-condensing.

DIMENSIONS: 12cm x 7.2cm x 2.4cm (4.7" x 2.8" x 1.0") W, D, H.

WEIGHT: 0.3kg (0.7lbs). INCLUDED ACCESSORIES: Power supply.

OPTIONS: RK-3T 19" rack adapter.

