



USB 1.1 Rover[®] 1850

1-Port USB 1.1 85m* Cat 5e Extender System

The USB 1.1 Rover 1850 extends USB 1.1 connections beyond the desktop up to 85* meters.

LEX (Local Extender)



Actual cable length
45.7cm (18")

REX (Remote Extender)



Actual cable length
15.2cm (6")

Features

The Rover 1850 uses technology ideal for extending USB peripherals including: keyboards, mice, interactive white boards, and game controllers and does not require external power adapters. Key features include:


- Remote extender supplies up to 400mA** to USB devices
- Supports both full-speed (12 Mbps) and low-speed (1.5 Mbps) throughputs
- Robust ESD and EFT immunity for industrial environments
- 3-year warranty

Includes the ExtremeUSB[®] suite of features:

- True plug and play; no software drivers required
- Supports all major operating systems: Windows[®], Mac OS X[®], and Linux[®]
- Reliable operation with all USB 2.0 and 1.1 devices, including hubs
- Patented USB extension technology

Applications

- Interactive white board
- Keyboard and mouse
- Sensor/data acquisition
- Industrial control



* Up to 40m for all USB devices; 85m is achievable for most low powered HID USB devices.

** 400mA when LEX is supplied with 700mA



4664 Lougheed Hwy.
Suite 221
Burnaby, BC,
V5C 5T5, Canada

www.icron.com
sales@icron.com
+1 604 638 3920



Specifications subject to
change without notification.

©2013

Icron Technologies Corp.
#90-00874-A04

USB 1.1 Rover® 1850 Specifications



Specifications subject to change without notification.
©2013
Icron Technologies Corp.
#90-00874-A04



RANGE

Full-Speed and Low-Speed:	Up to 40m (131 ft)
Low-Speed:	Up to 85m (279 ft)*

LEX (LOCAL EXTENDER)

USB Connector:	1 x USB Type A Plug
Pig Tail Length:	45.7cm (18")
Link Connector:	1 x RJ45
Dimensions:	85mm x 40mm x 22mm (3.34" x 1.57" x 0.87")
Enclosure Material:	Black ABS

REX (REMOTE EXTENDER)

USB Connector:	1 x USB Type A Receptacle
Pig Tail Length:	15.2cm (6")
Link Connector:	1 x RJ45
Maximum Current Available:	400mA when LEX is supplied with 700mA
Dimensions:	85mm x 40mm x 22mm (3.34" x 1.57" x 0.87")
Enclosure Material:	Black ABS

ENVIRONMENTAL

Operating Temperature:	0°C to 50°C (32°F to 122°F)
------------------------	-----------------------------

COMPLIANCE

Emissions:	FCC (Class A), CE (Class A)
Immunity:	CE Criteria A
Environmental:	RoHS2 (CE)
Safety:	CPSIA, Flammability V-1

SUPPORT

Warranty:	3 years
-----------	---------

* device and host dependant

Ordering Information

The USB 1.1 Rover® 1850 system includes a LEX, REX, Quick Start Guide and three year warranty.

For more information, email sales@icron.com or call +1 604 638 3920.

PART #	NAME	DESCRIPTION
00-00301	USB 1.1 Rover® 1850	1-Port 85m Cat 5e bus-powered USB Extender System