

## KDS-MP4

4K UHD Digital Signage Media Player













The KDS-MP4 is a high-quality LAN-based digital signage media player. The unit receives content from the Media Manager software installed on the PC, either via LAN or from an external USB memory stick, loads it into its internal memory and then displays it with image quality of up to 4K UHD via HDMI output.

## **FEATURES**

- 4K UHD Support.
- High Quality HDMI Video & Audio.
- Codec Format Support MPEG-1, MPEG-2, MPEG L2, MP3, H.264/MPEG-4, and VC-1.
- Memory Options 8GB internal.
- NTP Client For time synchronization.
- Integrated SMIL Control CMS device management in LAN environments.
- SMIL 3.0 Instruction (Sub-Set) Support.
- CMS Device Management In LAN environments using the integrated SMIL control.
- Perforated Side Panel For efficient heat dissipation.
- VESA Standard Mounting Bracket For mounting on-wall, inside a cabinet or to the VESA standard screw holes on the rear panel of a display.
- Media Manager Software For easy, powerful and versatile management of digital signage content via a PC.
- Media-Manager Multi-language Support Ready-made templates for screen layouts, logos, tickers and widgets.
- Compact DigiTOOLS® Built-in mounting bracket.

## **TECHNICAL SPECIFICATIONS**

I/O CONNECTORS: 1 HDMI, 2 USB 2.0, 1 Ethernet on a RJ-45 connector, 1 unbalanced stereo audio on a 3.5mm

mini jack, micro SD card slot.

VIDEO FORMAT POPAI Screen Media Standards SUPPORT: POPAI Screen Media Standards S6 (MPEG-1 SIF, 3Mbps CBR)

S7 (MPEG-1 480p, 10Mbps CBR) S8 (MPEG-1 720p, 15Mbps CBR) S9 (MPEG-2 480p, 6Mbps CBR) S10 (MPEG-2 720p, 12Mbps CBR) S11 (MPEG-4 AVC, 480p, 6Mbps CBR) S12 (MPEG-4 AVC, 720p, 10Mbps CBR) E4 (VC-1/WMV9, MP@ML, 720p)

E7 (MPEG-4 ASP, 480p, 10Mbps CBR) E8 (MPEG-4 AVC, 1080p, 10Mbps CBR).

IMAGE FORMAT POPAI Screen Media Standards

SUPPORT: S1 (JPEG 480p baseline)

S2 (JPEG 720p baseline) S3 (JPEG 1080p baseline) E1 (PNG 24bpp+alpha, 480p) E2 (PNG 24bpp+alpha, 720p) E3 (PNG 24bpp+alpha, 1080p).

AUDIO CODEC POPAI Screen Media Standards

SUPPORT: S4 (MPEG L2 audio)

S5 (MP3 audio, 320Kbps).

DYNAMIC CONTENT: W3C HTML5 (HTML, CSS, JavaScript)

W3C SMIL 3.0 instructions (sub-set).

INDICATORS: Power(green), Status(orange).

LOCAL STORAGE: 8 GB on-board flash memory (up to 6hrs of typical 720p video @3Mbps)

Micro SD card expansion slot.

POWER REQUIREMENT: 12V 1.5A DC.

POWER CONSUMPTION: 6W.

OPERATING 0° to 45°C (32° to 113°F).

TEMPERATURE:

STORAGE  $-40^{\circ}$  to  $+70^{\circ}$ C ( $-40^{\circ}$  to  $158^{\circ}$ F).

TEMPERATURE:

HUMIDITY: 10 - 85% @  $40^{\circ}$ C,  $32^{\circ}$  to  $104^{\circ}$ F non-condensing. DIMENSIONS:  $167 \text{mm} \times 118.8 \text{mm} \times 24.5 \text{mm}$  ( $6.57'' \times 4.67'' \times 0.96''$ ).

WEIGHT: 0.275kg (0.61lbs).

SAFETY: UL/FCC/CE/CCC/C-Tick/VCCI certified power supplies.

CERTIFICATIONS: CE/FCC/VCCI/TELEC/CCC/IC.

INCLUDED AC adapter, HDMI cable, 4 Velcro (2 sets).

ACCESSORIES:

WARRANTY: One-year limited parts & labor.