

Power Supply Models

AMX offers 5 variations of our Class I, CSA/CE approved, and UL listed system power supplies:

AMX PS/N POWER SUPPLIES		
PSN6.5	(FG423-41)	With U.S. power cord.
PS4.4	(FG423-44)	Includes U.S. power cord and barrel plug.
PSN4.4	(FG423-45)	Includes 2-pin captive-wire connector and U.S. power cord, with 3.5 mm captive-wire connector. (Discontinued, replaced by PSR4.4)
PSR4.4	(FG423-46)	Includes 2-pin retained captive-wire connector and U.S. power cord, with 3.5 mm captive-wire connector
PS3.0	(FG423-30)	Includes U.S. power cord and barrel plug.

NOTE: All models use an input connector sanctioned by the IEC (International Electrotechnical Commission).

PSN6.5 Specifications

FIG. 1 shows the front and rear panels of the PSN 6.5.



FIG. 1 PSN6.5 POWER SUPPLY

PSN6.5 SPECIFICATIONS	
Dimensions (HWD):	• 1 1/2" x 5 9/16" x 9 1/4" (3.81 cm x 14.10 cm x 23.50 cm)
Weight:	• 2.76 lbs. (1.25 kg) (without power cord)
Input:	• ~100-240 V, 2.6A MAX (1.3A MAX @ 230), 50/60 Hz
Output Voltage:	• 13.5 V $\overline{\text{DC}}$
Output Current:	• 6.5 A (continuous power output is 90 W max)
Ripple and Noise:	• 350 mV peak-to-peak @ 70% load
Protection:	• Over-voltage, over-current, short-circuit, transient and thermal switching regulated, overload protected
Power Indicator:	• Green LED indicates presence of DC on the output.
Connectors:	• Three removable 2-pin 3.5 mm mini-Phoenix connectors
Rear Panel Components:	• Three 12 V $\overline{\text{DC}}$ power supply connectors • Standard IEC (male) jack for the power cord
Input Power Cord:	• 6-foot (1.83 m) IEC cord with a grounded Edison plug for AC input (U.S. only)
Enclosure:	• Metal with black matte finish
Temp Range:	• 32°F - 122°F (0°C - 50°C)
Certification:	• UL: US listed - Class I Power Supply • CSA approved • CE approved • PSE approved • CCC approved
Accessories:	• Single Universal input power cord (64-0009) • 3 removable 2-pin 3.5 mm mini-Phoenix connectors (41-5025) • (Optional) AC-RK Accessory Rack Kit (FG515)

NOTE: The PSN6.5 replaces the (obsolete) PSN4.2 and PSN6.3 power supplies.

PS4.4, PSN4.4, and PSR4.4 Specifications

The PS4.4 power supply is identical to the PSN4.4 except that the PSN4.4 has a NetLinX-compatible 2-pin captive wire connector and the PS4.4 has a barrel-plug. The PSR4.4 comes with a NetLinX-compatible 2-pin retained captive wire connector.



Barrel-plug connector (FG423-44)



2-pin retained captive wire connector (FG423-46)

FIG. 2 PS4.4 POWER SUPPLIES (SHOWING DIFFERENCE IN CONNECTORS)

PS4.4, PSN4.4, AND PSR4.4 SPECIFICATIONS	
Dimensions:	• 4 5/8" x 2 1/4" x 1 1/2" (11.7 cm x 5.8 cm x 3.5 cm)
Weight:	• 1.1 lb. (499 g)
Input:	• ~100-240 V, 1.5A MAX (0.6A MAX @ 230), 50/60 Hz
Output Voltage:	• 13.5 V $\overline{\text{DC}}$
Output Current:	• 4.5A MAX
Ripple and Noise:	• 150 mV peak-to-peak @ full load
Protection:	• Over-voltage, over-current, short-circuit, transient and thermal. Switching regulated, overload protected.
Power Indicator:	• Green LED indicates the presence of V $\overline{\text{DC}}$ on the output.
Connectors:	• PS 4.4 - Barrel plug (see <i>Barrel Plug Dimensions</i>) • PSR4.4 - 2-pin retained captive wire connector (3.5 mm) • PSN4.4 (discontinued)- Mini 2-pin captive wire connector (3.5 mm)
Input Power Cord:	• 6-foot (1.83 m) IEC cord with a grounded Edison plug for AC input (U.S. only)
Enclosure:	• Molded black matte plastic
Temp Range:	• 32°F - 104°F (0°C - 40°C)
Certification:	• UL: US listed - Class I Power Supply • CSA approved • CE approved • PSE approved
Accessories:	• Single Universal input power cord (64-0009) (Included)
PS4.4 Plug Dimensions:	• 2.1 mm ID • 5.5mm OD • 9.5mm length

PS3.0 Specifications

FIG. 3 shows the PS3.0. The PS3.0 is a Class I power supply which is CE approved and UL listed. The PS3.0 uses a barrel-plug connector.



FIG. 3 PS3.0 POWER SUPPLY

PS 3.0 SPECIFICATIONS	
Dimensions (HWD):	• 3 7/8" x 1 3/4" x 1 1/4" (9.8 cm x 4.5 cm x 3.1 cm)
Weight:	• 5.6 oz (150 g) (without power cord)
Input:	• ~100-240 V, 3A MAX, 50/60 Hz
Output Voltage:	• 12 V $\overline{\text{---}}$
Output Current:	• 3.0 A
Ripple and Noise:	• 200 mV (60Hz Ripple + Switching ripple and noise)
Protection:	• Over-voltage, over-current, short-circuit, transient and thermal switching regulated, overload protected
Power Indicator:	• Green LED indicates presence of DC on the output.
Connectors:	• 1.3mm barrel plug, 11mm long
Input Power Cord:	• 6-foot (1.83 m) IEC power cord terminated with a grounded Edison plug for AC input (U.S. only).
Enclosure:	• Metal with black matte finish
Temp Range:	• Operating temperature: 32°F - 122°F (0°C - 50°C) • Storage temperature: -4°F - 185°F (-20°C - 85°C)
Certification:	• UL: US listed - Class I Power Supply • CUL approved • TUV approved • FCC approved • CE approved • PSE approved
Accessories:	• Single Universal input power cord (64-0009 - Included)



Last Revised: 12/02/2015

© 2015 Harman. All rights reserved. AMX, AV FOR AN IT WORLD, and HARMAN, and their respective logos are registered trademarks of HARMAN. Oracle, Java and any other company or brand name referenced may be trademarks/registered trademarks of their respective companies. AMX does not assume responsibility for errors or omissions. AMX also reserves the right to alter specifications without prior notice at any time. The AMX Warranty and Return Policy and related documents can be viewed/downloaded at www.amx.com.

3000 RESEARCH DRIVE, RICHARDSON, TX 75082 AMX.com | 800.222.0193 | 469.624.8000 | +1.469.624.7400 | fax 469.624.7153

AMX (UK) LTD, AMX by HARMAN - Unit C, Auster Road, Clifton Moor, York, YO30 4GD United Kingdom • +44 1904-343-100 • www.amx.com/eu/

93-0423-41 REV: N



9 3 - 0 4 2 3 - 4 1