

PSE-1

10Gb UHD Power Over Ethernet Injector





The PSE-1 provides power remotely over Ethernet to any device capable of acting as a PoE acceptor (for example, a wallplate, where it may be difficult to connect an external power supply). This allows a single HDBT LAN cable to provide both data and electrical power to compatible devices.

FEATURES

- Total Range Up to 100m (328ft) @4K on shielded BC-DGKat623 or BC-HDKat6a cable (or equivalent).
- 48V DC Power.

TECHNICAL SPECIFICATIONS

INPUT/OUTPUT: 1 HDBaseT/LAN + POE on an RJ-45 connector, 1 HDBaseT/LAN on an

RJ-45 connector.

OPERATION BANDWIDTH: Up to 10.2Gbps (3.4Gbps per data channel).

COMPLIANCE WITH HDMI STANDARD: Supports HDMI, HDCP. INDICATOR LEDS: ON, POE STATUS.

POWER SOURCE: 48V DC, 240mA (device plus remote power sink).

POWER PROVISION: Up to 13W.

OPERATING TEMPERATURE: 0° to +40°C (32° to 104°F).

STORAGE TEMPERATURE: -40° to +70°C (-40° to 158°F).

HUMIDITY: 10% to 90%, RHL non-condensing.

COOLING: Convection, vents.

ENCLOSURE TYPE: Aluminium.

DIMENSIONS: 12.1cm x 6.99cm x 2.47cm (4.76" x 2.75" x 0.97") W, D, H.

RACK MOUNT: With optional adapter.

FURNITURE MOUNT: With included rubber feet.

PRODUCT WEIGHT: 0.23 kg (0.51lbs) approx.

SHIPPING WEIGHT: 0.72kg (1.59lbs) approx.

VIBRATION: ISTA 1A in carton (International Safe Transit Association).

Complies with appropriate requirements of RoHs and WEEE.

SAFETY REGULATORY COMPLIANCE: CE, c-UL, UL.

EMI/EMC REGULATORY COMPLIANCE: CE, C-tick, FCC Class A, ICES, KCC, VCCI.

ENVIRONMENTAL REGULATORY

COMPLIANCE:

INCLUDED ACCESSORIES:

Power supply.

OPTIONS: RK-3T 19" rack adapter. WARRANTY: 7 years parts and labor.