

RC-54DL

12button KNET™ Auxiliary Keypad with Knob and Displays (US)



The RC54DL is a 12button auxiliary keypad, with knob and LCD displays. Connected over KNET™ to master control keypad such as RC74DL, the RC54DL is ideal for serving as remote secondary keypad in classrooms, boardrooms or auditoriums, for convenient control of their multimedia devices

FEATURES

Back Lit & Label Capable Buttons - 6 RGBcolor, tactile feedback, backlit buttons. Buttons are grouped in 2 groups, 4 buttons in 'SOURCES' group, and 2 buttons in 'DISPLAY' group

Custom Labeled, Removable Button Caps

Volume Control Knob with LEDs - Bidirectional rotary dialed digital knob for volume control, with 5 LED bar for visual volume level feedback

LCD Displays - 3 bluecolor and 8 whitecharacters LCD displays, in 3 button groups, for programmed visual feedback indication and group configured labeling, such as knob control state of either audio or light level

2 K-NET™ Connectors - Connects to master room controller, and auxiliary keypads for remote keypad control

K-NET™ Single Link Connection - Provides a single keypad link cableconnectivity, carrying both power and keypad control communication information

Program Control - Program configuration with Kramer KConfig software

Keypad Lock-Out - Option for tampering prevention by locking and unlocking of the keypad buttons **Mini USB Port** - To upload configuration files, set the KNET™ ID number, and power the device during configuration

Mounting - Inwall, in standard 3 gang US wall junction boxes

Easy Installation - Fits to standard inwall boxes for simple and costreducing installation



TECHNICAL SPECIFICATIONS

PORTS: 2 KNET on terminal block connectors, 1 mini USB for programming

POWER 12V DC, 420mA

CONSUMPTION:

OPERATING TEMPERATURE:

0° to +40°C (32° to 104°F)

STORAGE

40° to +70°C (40° to 158°F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL noncondensing

DIMENSIONS: 16.2cm x 2.3cm x 11.4cm (6.4" x 0.9" x 4.5") W, D, H

WEIGHT: 0.15kg (0.33lbs)

SHIPPING WEIGHT: 0.65kg (1.43lbs)

SHIPPING DIMENSIONS:

35.1cm x 21.2cm x 7.2cm (13.8" x 8.4" x 2.8") W, D, H

INCLUDED

ACCESSORIES:

Power supply, label set, screwdriver



CONFIGURATIONS

RC-54DL(W)	US-size RC-54DL, White Design Frame, Label Set
RC-54DL/JP(W)	US-size RC-54DL, White Design Frame, Label Set
RC-54DL(G)	US-size RC-54DL, Gray Design Frame, Label Set
RC-54DL/JP(G)	US-size RC-54DL, Gray Design Frame, Label Set
RC-54DL(B)	US-size RC-54DL, Black Design Frame, Label Set
RC-54DL/JP(B)	US-size RC-54DL, Black Design Frame, Label Set
RC-54DL(BAL)	US-size RC-54DL, Brushed Aluminum Design Frame, Label Set
RC-54DL/JP(BAL)	US-size RC-54DL, Brushed Aluminum Design Frame, Label Set

