



## SK21P-3

HighSecLabs Secure 2-Port, DisplayPort  
KVM Switch

| HDMI | C-KVM



SK21P-3 is a secure 2-port, small-form-factor DisplayPort KVM switch. It allows users to share peripherals – keyboard, mouse and monitor – between two different security-level networks/computers. It provides the highest possible isolation between two connected computers and is NIAP Common Criteria Protection Profile version 3.0 (PP3.0) certified

## FEATURES

**Small Form Factor** - Occupies minimum desktop space

**DisplayPort Video Support** - DisplayPort 1.2 with resolutions up to 3840×2160 30bpp @60Hz, 17.28Gbps on 4-lane link; two computers connected to a single display

**AUX Channel Protection** - Patented AUX channel firewall technology prevents leakage, signaling attacks prevented by design, fully functional EDID

**Highest Security by Design** - NIAP Common Criteria PP3.0 for Peripheral Sharing Switch (PSS) devices

**Hardware-Based Peripheral Isolation** - No dependency on firmware or software, all firmware on ROM, no keyboard buffering or memory

**Unidirectional Optical Data Diodes** - Assures USB peripheral isolation, data flows from devices to host only

**Peripheral Security** - Full USB device filtering to assure support for keyboard and mouse only

**Active Anti Tampering System** - Always-on with 10 years battery, holographic tampering evident labels



# KRAMER

## TECHNICAL SPECIFICATIONS

---

CONSOLE PORTS:	1 x HDMI 1.4 connector, 2 USB-A connectors for keyboard and mouse, 1 3.5mm mini jack for unbalanced stereo audio, 1 3.5mm mini jack connector for control (RDC)
COMPUTER PORTS:	2 DisplayPort 1.2 connectors, 2 USB-B connectors for keyboard and mouse, 2 3.5mm mini jacks for unbalanced stereo audio
MAX RESOLUTION:	4K30 UHD (3840X2160 @30Hz)
WARRANTY:	3 years
POWER REQUIREMENTS:	12V DC, 1.5A
POWER TYPE:	External
OPERATING TEMPERATURE:	32° to 104°F (0° to 40°C)
STORAGE TEMPERATURE:	-4° to 140°F (-20° to 60°C)
HUMIDITY:	0-80% RH, non-condensing
SUPPORTED OS:	Windows, Linux, Mac
SECURITY CERTIFICATION:	NIAP Common Criteria PP3.0 for Peripheral Sharing Switch (PSS) devices
PRODUCT CERTIFICATION:	CE, RCM, FCC class B, VCCI, TUV US, TUV Canada
PRODUCT LIFE-CYCLE:	10 years
PRODUCT DIMENSION:	17.70cm x 8.20cm x 3.50cm (6.97" x 3.23" x 1.38" ) W, D, H
PRODUCT WEIGHT:	0.5kg (1.1lbs) approx
SHIPPING DIMENSION:	24.50cm x 20.50cm x 8.50cm (9.65" x 8.07" x 3.35" ) W, D, H
SHIPPING WEIGHT:	0.8kg (1.8lbs) approx