



STBi3



STBi3 is an IP decoder supporting H.264/H.265 UDP and RTP streams via 100Mb/copper with HDMI output. RF tuner for decoding QAM signals over coax. Supports PoE. STBi3 auto-discovers the ZyPerMX, ZyPerMX2/4, HDBridge and ZvPro iSeries streams, which are sold separately. Includes IR remote and batteries, IR pigtail, universal power supply, and HDMI cable

TECHNICAL SPECIFICATIONS

Network Service	Ethernet 10/100/1000 LAN – 1 RJ45
Interface	Power DC connector – 12 VDC 1A (Worldwide AC adapter is supplied) PoE Power Standard PoE+ – RJ45 LAN Connector Video output HDMI – Up to 1080p60/60Hz Recommended stream data rates MPEG2 – <=24Mbps, MPEG4 <= approx 6-8MBps Audio output HDMI – Available on HDMI connector USB port USB host – 2 USB2.0 normal type (Type A) QAM and ATSC 2.0 input AUS QAM and ATSC 2.0 tuner input – 1 F Connector Remote control receiver IR port – 3.5mm port. External IR Receiver included
Certification for Use	Standard CE – Yes, RoHS – Yes, FCC – Yes
Product Dimensions	14.10cm x 3.50cm x 8.90cm (5.55" x 1.38" x 3.50") W, D, H
Product Weight	0.1kg (0.3lbs) approx
Shipping Dimensions	44.00cm x 41.50cm x 26.00cm (17.32" x 16.34" x 10.24") W, D, H
Shipping Weight	0.6kg (1.2lbs) approx

