



## TP-874xr

4K HDR HDMI PoC Receiver with RS-232 & IR over Long-Reach DGKat 2.0

| HDMI | DGKat | 4K/60 UHD (4:4:4)



TP-874xr is a high-performance, long-reach DGKat™ 2.0 receiver for 4K@60Hz (4:4:4) HDR HDMI HDCP 2.2 signals, RS-232 and IR signals and 2-way powering over twisted pair. It converts the transmitted DGKat™ 2.0 signal into an HDMI, RS-232 and IR signals. TP-874xr extends the signal to up to 50m (160ft) at 4K@60Hz (4:4:4) resolution and up to 70m (230ft) at 4K@30Hz (4:4:4) 24bpp resolution over Kramer shielded cables

## FEATURES

- High Performance Extender** - Professional DGKat™ 2.0 receiver for providing long-reach signals and 2-way power over twisted pair copper infrastructures. TP-874xr employs low-level video compression technology that delivers visually lossless performance for 4K@60Hz (4:4:4) HDR signals with near-zero latency. It converts the transmitted DGKat™ 2.0 signal into an HDMI signal
- HDMI Signal Extension** - HDR, HDCP 2.2 compliant. Supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0
- EDID Pass-through** - Pass-through algorithm ensures Plug and Play operation for HDMI source and display systems
- Multi-channel Audio Extension** - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound
- Bidirectional RS-232 Extension** - Serial interface data flows in both directions, allowing data transmission and device control
- Bidirectional Infrared Extension** - IR interface data flows in both directions, allowing remote control of peripheral devices located at either end of the extended line
- Cost-effective Maintenance** - Status LED indicators for HDMI and DGKat™ 2.0 ports facilitate easy local and remote maintenance and troubleshooting
- Easy Installation** - Single twisted-pair cable for signal and power wiring. Compact DigiTOOLS® fan-less enclosure for device-back mounting, or side-by-side mounting of 3 units in a 1U rack space with the recommended Kramer rack adapter



# kramer

## TECHNICAL SPECIFICATIONS

---

Inputs	1 DGKat 2.0 On an RJ-45 female connector
Outputs	1 HDMI On an HDMI female connector
Ports	1 RS-232 On a 3-pin terminal block connector 1 IR On a 3.5mm mini jack connector
Video	Transmitted Data Bandwidth: Up to 18Gbps (6Gbps per graphic channel) Max Resolution at High Compression Level 3840x2160@60Hz (4:4:4) 24bpp Max Resolution at Standard Compression Level 4096x2160@60Hz (4:4:4) 24bpp Standards Compliance: HDR10, HDCP 2.2  HDMI Support Deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0
High Compression Reach Extension	Using Shielded UNIKAT Cables Up to 50m (160ft) at 4K@60Hz (4:4:4), Up to 70m (230ft) at 4K@30Hz (4:4:4) or full HD (1080p @60Hz 36bpp)  Using Plenum HDKat Cables Up to 40m (130ft) at 4K@60Hz (4:4:4), Up to 50m (160ft) at 4K@60Hz (4:2:0) or full HD (1080p @60Hz 36bpp)
Standard Compression Reach Extension	Using Shielded UNIKAT Cables Up to 35m (110ft) at 4K@60Hz (4:4:4), Up to 70m (230ft) at 4K@30Hz (4:4:4) or full HD (1080p @60Hz 36bpp)
Extension Line	Signal Compression: Standard or high compression level applied to >1080p signals  Compliance: DGKat 2.0
User Interface	Indicators: IN, OUT, and ON LEDs  Controls Dip-switches to define compression level
Power	Source: 12V DC, 2A  Consumption: (connected to power and providing power to a transmitter) 0.87A
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F)  Storage Temperature: -40° to +70°C (-40° to 158°F)  Humidity: 10% to 90%, RHL non-condensing
Enclosure	Size DigiTOOLS  Type Aluminum  Cooling Convection ventilation
Accessories	Included 1 power adapter with cord, 1 bracket set
REGULATORY	Safety CE, UL  Environmental RoHs, WEEE
Product Dimensions	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
Product Weight	0.2kg (0.5lbs) approx
Shipping Dimensions	49.00cm x 18.60cm x 58.80cm (19.29" x 7.32" x 23.15" ) W, D, H

Shipping Weight

0.7kg (1.5lbs) approx

