

UETAX can be used for outdoor interviews in any weather.









©Earned [Anta-ga-taisyo (You are the Grand Prize)], FNS Technical Award

©Earned [Highest Award] in Technology Sector, Japan Commercial Broadcasters Association Prize / 2016

Model	Waterproof Electret Type	
Model Number	UM230C UM230CT	
Front Sensitivity	- 62dB	
Frequency Response	80Hz to 15KHz	
Directivity	Omnidirectional	
Output Impedance	600Ω (Balanced)	
Max. Sound Pressure Level	110dB, SPL	
Phantom Power Source	20V to 48V	
Size	Ф1.30in. x 9.05in. (33Ф x 230mm (L))	
Mass	3.95oz (112g)	4.73oz(134g)
Service Temperature	32.00°F to 104.00°F (0°C to 40°C)	
Connector	XLR (male)	Waterproof 3-pin Connector (female)
Case	Aluminum Body, UETAX Gray-Metallic Glazed Finish, BLUELINE	
Accessories	Wind Screen, 9.84ft (3m) Cable, Instruction Manual	

**%**Patented



The UM230 is perfect for radio/television broadcast audio no matter the environment. Sound quality is crystal clear courtesy of our patented omni-directional tuning.

With a solid, and lightweight aluminum design, the UM230 is durable

and never fails to securely pick up target voices.

## Two connector types are available.



Worldwide Dealer

## FOR-A COMPANY LIMITED www.for-a.com



USA Western (CA), Eastern & Midwest (NJ), Southern (FL), Latin America & Caribbean (FL), Canada (Toronto), Europe (Milan), UK (London), Italy (Milan), Middle East-Africa (Dubai), Korea (Seoul), China (Beijing), South-East Asia (Hong Kong), India (Mumbai)



## **UETA**X

www.uetax.co.jp

•Please access our website for the detailed specification and technical data of products, etc.

**UETAX Corporation** 83-8 Iwaki Jouetsu City, Niigata, 943-0814 Japan PHOHE: +81-25-525-9666