



## VCO-5UHD

5-Port 4K60 4:2:0 HDMI Video Content  
Overlay Solution

| HDMI | Ethernet - RJ-45



VCO-5UHD is a video content overlay solution that overlays five independent graphic images to any number of displays over standard HDMI in resolutions up to 4K60 (4:2:0). This enables the display of individual, targeted messages for each and every display in your installation

### FEATURES

- 4K60 4:2:0 Overlays - Static or animated, dynamic color image
- Overlays Any Size Content - With full transparency control
- Multiple Overlay Templates - For multiple applications
- Selectable Looping Output - For daisy-chaining any number of displays
- Centralized Control of all Promotional Overlays
- Error Reporting - Comprehensive error reporting for connected displays and overlays
- Full Overlay Automation - Automates entire overlay process from design to display, in multiple locations
- Easy to Use - Feature-rich software – design, schedule, and display
- Enables Digital Signage with Unlimited Viewing Zones



# KRAMER

## TECHNICAL SPECIFICATIONS

---

Inputs	1 HDMI On a female HDMI connector 1 USB On a female USB Type-A connector
Outputs	5 HDMI On female HDMI connectors 1 Loop HDMI On a female HDMI connector
Ports	Ethernet 10/100BaseT On an RJ-45 connector
Video	Max Resolution 4K60 (4:2:0)
General	Controls IP address setup DIP-switches, Reset/Test button, Ethernet (VCO Setup App), output status indication LEDs, input indication LED, loop indication LED
Power	Consumption 5V DC, 1.6A
Environmental Conditions	Operating Temperature 0° to +40°C (32° to 104°F) Storage Temperature -40° to +70°C (-40° to 158°F) Humidity 10% to 90%, RHL non-condensing
Accessories	Included: Power cord, rack ears, cable bracket, plastic cable ties
PRODUCT DIMENSION:	21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72" ) W, D, H
PRODUCT WEIGHT:	0.0kg (0.0lbs) approx
SHIPPING DIMENSION:	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83" ) W, D, H
SHIPPING WEIGHT:	0.0kg (0.0lbs) approx

