



VIA Connect²

Wireless and Wired Presentation and Collaboration Platform

| HDMI | Ethernet - RJ-45 | 4K/60 UHD (4:2:0)



VIA Connect² is a smart, secure, wireless and wired presentation and collaboration platform that makes it simple to get actual work done during meetings and classes. With any laptop or mobile device, users can view, edit, and comment on documents in real time sessions. Meeting participants can display or stream full, uninterrupted video up to 4K@60Hz from their device, and even play YouTube® videos in full frame rate. Up to four participants can share their screens simultaneously on the main display either using the VIA app mirroring feature, iOS mirroring via AirPlay™, Windows & Android mirroring via Miracast™, or ChromeBook mirroring.

VIA Connect² supports 3rd party conferencing and apps, such as Microsoft Teams®, and Zoom®. The platform can handle most small to medium size meeting spaces and is ideal for classrooms and huddle spaces. VIA Connect² is super-compact (74x74mm) and flexible to install with both built-in Wi-Fi and LAN connectivity and includes industry-leading 1024-bit encryption for secure use on the internal network

FEATURES

Quick and Reliable Wireless Connectivity - A simple and intuitive user interface enables iOS™, Android™, Chromebook™, PC, and Mac™ device users to instantly connect to a main display. 2.4GHz/5GHz Wi-Fi and MIMO antennas establish and maintain a fast and reliable connection

Clientless Connectivity - Airplay, Miracast, Join Through Browser

Up to 4K@60 HDMI Wired Input - Enables hard-wiring, auto switching, for connecting a computer or any HDMI compatible device camera, multimedia player or computer that supports HDCP signals

Powerful Security Feature - 802.1x User authentication, 1024-bit encryption, dynamic room code
Built-In Wi-Fi and LAN

Comprehensive Collaboration Functionality - Whiteboard, filesharing, View Main Display, chat, etc

High-Quality Video Streaming - Supports up to 4K@60Hz resolution using the VIA app Multimedia feature

Simultaneous Display - Four participants can simultaneously present content on the main display

Seamless Live Video Streaming - Stream live content from meeting rooms, classrooms and studios using RTMP/RTMPS to all the leading platforms, like YouTube™, Kaltura™, Panopto™ and more

Optimized for Video Conferencing - VIA Versa feature allows users to wirelessly connect to the professional grade camera and AV in their meeting spaces easily and instantly

Wireless USB - Supports Microphone, Speaker & Camera

Built-in Third Party VC integration for Zoom™ & Teams™

Cloud-Based Management - Seamlessly compatible with VIA Site Management (VSM)

Easy and Flexible Installation - With a super-compact form factor, it can be discreetly installed on the back of a display, projector or almost anywhere



TECHNICAL SPECIFICATIONS

| | |
|--|---|
| Ports | 1 Ethernet: On an RJ-45 connector 2 USB 3.0: On a female USB type-A connector 1 USB 2.0: On a female USB type-A connector 2 Pin connector: Video Switching control |
| Outputs | 1 HDMI 2.0 : |
| Inputs | 1 HDMI 2.0 : |
| Video | Max Resolution: up to 4K@60 for both Input & Output |
| General | Processor: Intel® Gemini Lake QC SOC Memory: 4GB LPDDR4 (2400) Storage: 32GB eMMC Networking: 1 x Gigabit LAN Wi-Fi 802.11 ac/b/g/n dual band Operating System: Linux |
| Power | Input Source: 12V DC Consumption: 1.3A |
| Environmental Conditions | Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing |
| Regulatory Compliance (Standards Compliance) | Safety: CE |
| Enclosure | Type: Aluminum Cooling: Fan with sink Kensington lock : |
| Accessories | Included: Power adapter, Video Switching control cable, VESA mount |
| Product Dimensions | 7.00cm x 7.00cm x 3.34cm (2.76" x 2.76" x 1.31") W, D, H |
| Product Weight | 0.2kg (0.4lbs) approx |
| Shipping Dimensions | 15.20cm x 12.00cm x 8.50cm (5.98" x 4.72" x 3.35") W, D, H |
| Shipping Weight | 0.6kg (1.3lbs) approx |



