



Key Features

- Long-lasting laser phosphor light source | 5,200 lumen brightness | Large images in small spaces |
- Ultra-high contrast ratio | Secure MHL/HDMI port




Product Description

Featuring 1280x800 WXGA resolution and 5,200 lumens of brightness, the ViewSonic® LS810 Laser Projector is the ideal solution for modern business and education environments. Designed with a laser phosphor light source lasting up to 20,000 hours, this projector delivers long-term, virtually maintenance-free usage for any boardroom or classroom. With its 0.23 ultra-short throw ratio, HV keystoneing and 4 corner adjustments, the LS810 makes installation a hassle-free experience. What's more, the ultra-short throw ratio allows you to place the projector just inches away from a wall or screen to give you a huge image for less cost than a comparably sized display. The LS810 also features a hidden PortAll® compartment which accommodates additional accessories such as a wireless streaming device, or PC stick. Powered by SuperColor™ technology for true-to-life images, and SonicExpert® technology for incredibly clear sound, the LS810 delivers an immersive audiovisual performance.




- | | | | | |
|--------------------|-----------------|--------------------------|-----------------|-------------------------|
| 1. Menu Controls | 5. AC In | 9. Video In | 13. Audio In | 17. Speakers (10W x2) |
| 2. Projection Lens | 6. RS232 | 10. USB Type A (powered) | 14. 12V Trigger | 18. Elevation Feet |
| 3. HDMI | 7. Monitor Out | 11. USB Mini B | 15. Audio Out | 19. PortAll® (HDMI/MHL) |
| 4. VGA x2 | 8. Component In | 12. Menu Controls | 16. LAN | |



1280 x 800
RESOLUTION



5,200
LUMENS



0.23
THROW RATIO

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

| | |
|--|---|
| Throw Distance: | 1.21 – 2.62 ft. / 0.37 – 0.8 m |
| Throw Ratio: | 0.23 |
| Type: | Laser DLP |
| Lens: | Digital optical focus |
| Keystone: | Vertical ($\pm 30^\circ$) / Horizontal ($\pm 30^\circ$) |
| Light Source (watt): | 390 |
| Light Source Life, Normal (hours): | 15000 |
| Light Source Life, Dynamic Eco-Mode (hours): | 20000 |
| Brightness (ANSI Lumens): | 5,200 |
| Color Depth: | 30 bits, 1.07B Color (10+10+10) |
| Resolution: | 1280 x 800 |
| Dynamic Contrast Ratio: | 100000:1 |
| Aspect Ratio: | 16:10 |
| Resolution Type: | WXGA |
| Display Size (in.): | 70 – 150 in. / 1.78 – 3.81 m (diagonal) |

Video Signal:

| | |
|-----------------------|-----------|
| Frequency Horizontal: | 15–100KHz |
| Frequency Vertical: | 24–120Hz |

Compatibility:

| | |
|------------------------|---|
| PC Resolution (max): | Up to 1920x1080 |
| Mac® Resolution (max): | Up to 1920x1080 (may require MAC adapter) |

Connector:

USB 2.0 Type A(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), HDMI 1.4(1), HDMI MHL(1), VGA In(2), VGA Out(1), Composite RCA Video In(1), Component RCA(1), S-Video In(1), Mini USB(1), Micro USB(1)

Audio:

| | |
|--------------------|---------|
| Internal Speakers: | 8W (x2) |
|--------------------|---------|

Power:

| | |
|--------------------|----------------------------------|
| Voltage: | AC 100-240V (universal), 50-60Hz |
| Consumption (max): | 450W |
| Stand-by: | <0.5W |

Controls:

| | |
|--------------------|--|
| Physical Controls: | Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source |
| On Screen Display: | Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) |

Operating Conditions:

| | |
|----------------------------|---------------------|
| Temperature: | 32-104° F (0–40° C) |
| Humidity (non-condensing): | 0-90% |

Weight (imperial):

| | |
|--------------|-------|
| Net (lbs): | 22.05 |
| Gross (lbs): | 33.07 |

Weight (metric):

| | |
|-------------|------|
| Net (kg): | 10.0 |
| Gross (kg): | 15 |

Dimensions (metric) (WxHxD):

| | |
|-----------------|-----------------|
| Packaging (mm): | 550 x 570 x 310 |
| Physical (mm): | 508 x 392 x 165 |

Dimensions (imperial) (WxHxD):

| | |
|------------------|----------------------|
| Packaging (in.): | 21.65 x 22.44 x 12.2 |
| Physical (in.): | 20.0 x 15.4 x 6.5 |

General:

Regulations: Mexico Energy test/Registration, EAC, TUV-S Mark (Argentina), India BIS, FCC, CE, EMC, CB, CCC, RoHS, REACH, SVHC, WEEE, ErP, Mexico NOM, cTUVus, PSB, RCM, CECP

PACKAGE CONTENTS: LS810 projector, power cable, VGA cable, HDMI Cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty: 3-year limited warranty on parts and labor, 1st year free Express Exchange® service**

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907847413

Accessories:

BCP100, BCP120, HB10B, PGD-350, PJ-WMK-006, VIEWSTICK2, VIEWSYNC3, WPG-300