

VM-1120

1:10 Balanced Stereo Audio Distribution Amplifier



The VM-1120 is a high-performance distribution amplifier for balanced mono audio signals on XLR connectors. It can also be configured as a 1:20 distribution amplifier for mono balanced audio signals

FEATURES

Grouped Audio Level Controls

Dual Mode - Configure as 1:20 (mono) or 1:10 (stereo) DA

S/N Ratio - 89.3dB

Standard 19" Rack Mount Size - 2U



TECHNICAL SPECIFICATIONS

INPUTS: 2 balanced stereo or 4 balanced mono audio, +4dBu/50k on XLR (F) connectors

OUTPUTS: 10 balanced stereo or 20 balanced mono audio, +4dBu/50 on XLR (M) connectors

MAX. OUTPUT

LEVEL:

23.8Vpp

BANDWIDTH (-3dB): >100kHz

S/N RATIO: 89.3dB

CROSSTALK: 78dB

CONTROLS: Level (x4): 0.7dB to +5.1dB, mode selector switches

COUPLING: AC (input); DC (output)

AUDIO THD + NOISE: 0.081%

AUDIO 2nd 0.006%

HARMONIC:

POWER

230V AC, (115V AC USA), 15VA

CONSUMPTION:

INCLUDED ACCESSORIES:

Power cord

19" x 7.24 x 2U (43.6cm x 18.40cm 8.80cm) W, D, H

PRODUCT DIMENSION:

PRODUCT WEIGHT: 3.8kg (8.3lbs) approx

SHIPPING DIMENSION:

55.00cm x 29.40cm x 16.10cm (21.65" x 11.57" x 6.34") W, D, H

SHIPPING WEIGHT: 4.9kg (10.8lbs) approx

