



# KRAMER

## VM-114H4C

2x1:4 HDMI/Twisted Pair Switcher & Twisted Pair Distribution Amplifier



The VM-114H4C is a high-performance switcher and distribution amplifier for HDMI and DGKat™ twisted pair signals. It reclocks and equalizes one of two selectable input signals (HDMI or DGKat twisted pair) and distributes it to four DGKat twisted pair outputs.

## FEATURES

- Max. Data Rate - 4.95Gbps (1.65Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant.
- DGKat™ Signal Integration - Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables. We strongly recommend using Kramer DGKat™ cables designed specifically for optimum performance.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- HDMI Support - x.v.Color™, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD (only on the TP inputs and outputs).
- 3D Pass-Thru.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- System Range - Up to 90m (295ft) at 1080i, or up to 30m (98ft) at 1080p on shielded BC-DGKat524 cable. Up to 90m (295ft) at 1080i, or up to 50m (164ft) at 1080p on shielded BC-DGKat623 cable. Up to 100m (330ft) at 1080i or up to 90m (295ft) at 1080p on shielded BC-DGKat7a23 cable.
- Cable - Requires STP (shielded twisted pair) cable. For optimum range and performance, use Kramer's BC-DGKat524, BC-DGKat623 or BC-DGKat7a23 cables. Note that the transmission range depends on the signal resolution, source device and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground.
- Active Input & Output LED Indicators.
- Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 90m (270ft) of each other.
- Flexible Control Options - Front panel buttons, RS-232, infrared control sensor, remote included.

## TECHNICAL SPECIFICATIONS

INPUTS:	1 HDMI connector, 1 DKGat twisted pair on an RJ-45 connector.
OUTPUTS:	4 DKGat twisted pairs on RJ-45 connectors.
MAX. DATA RATE:	4.95Gbps (1.65Gbps per graphic channel).
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
CONTROLS:	Input select button, EDID select button, panel lock button.
INDICATOR LEDs:	IR communication, power, IN 1 (HDMI), IN 2 (CAT 5), OUTPUT 1, 2, 3 and 4.
POWER CONSUMPTION:	12V DC, 2A.
DIMENSIONS:	21.5cm x 16.3cm x 4.4cm (8.5" x 6.4" x 1.7") W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
INCLUDED ACCESSORIES:	Power supply, bracket installation kit, RC-IR3 infrared remote control transmitter.
OPTIONS:	RK-1 19" rack adapter.

