

VM-3AN

1:3 Balanced Stereo Audio Distribution Amplifier



The VM-3AN is a high-performance distribution amplifier for balanced stereo audio signals. The unit takes one stereo input and distributes the signal to three identical outputs

FEATURES

S/N Ratio - 90dB

L & R Level (Gain) Controls



TECHNICAL SPECIFICATIONS

INPUT: 1 balanced stereo audio on a 5pin terminal block

OUTPUTS: 3 balanced stereo audio on 5pin terminal blocks

MAX. OUTPUT

LEVEL:

Audio: 18.5Vpp

BANDWIDTH (-3dB): >100 kHz

S/N RATIO: 90dB @1kHz

CONTROL: Output level control:77 to +6dB, R+/, L+/ channels

AUDIO THD + NOISE: 0.008%

AUDIO 2d 0.001%

HARMONIC:

POWER

.....

CONSUMPTION:

ION:

12V DC, 89mA

PRODUCT

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

DIMENSION:

PRODUCT WEIGHT: 0.2kg (0.4lbs) approx

SHIPPING 15.7

15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

DIMENSION:

SHIPPING WEIGHT: 0.5kg (1.1lbs) approx

INCLUDED F

ACCESSORIES:

Power supply

OPTIONS: RK3T 19" rack adapter

