

VM-400HDCPxI

1:4 4K60 4:2:0 DVI DA

| DVI | HDCP Compliant | 4K/60 UHD (4:2:0)



The VM400HDCPxI is a 4K@60Hz (4:2:0) 1:4 distribution amplifier for HDMI signals via singlelink DVI. It takes one DVI input, equalizes and reclocks the signal and distributes it to four identical outputs. With the appropriate adapter, it distributes signals having resolutions up to 4K@60Hz (4:2:0), WUXGA and 1080p

FEATURES

Max. Data Rate - 10.2Gbps (3.4Gbps per graphic channel)

Resolution Support - Up to 4K@60 (4:2:0), WUXGA and 1080p

HDCP Compliance

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal integrity to travel longer distances

I-EDIDPro™ Kramer Intelligent EDID Processing™ - An intelligent EDID handling and processing algorithm that ensures Plug and Play operation for HDMI systems

Default EDID - For fast and efficient connection of the unit

3D Pass-Through

USB Port - For firmware upgrading



TECHNICAL SPECIFICATIONS

INPUT: 1 DVII connector

OUTPUTS: 4 DVII connectors

PORT: 1 USB for firmware upgrade

MAX. DATA RATE: 10.2Gbps (3.4Gbps per graphic channel)

STANDARDS

COMPLIANCE:

Supports HDMI and HDCP

CONTROLS: **EDID Setup button**

INDICATOR LEDs: IN, OUT 1 to 4 LEDs

OPERATING TEMPERATURE: 0° to +40°C (32° to 104°F)

STORAGE 40° to +70°C (40° to 158°F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL noncondensing

PRODUCT

DIMENSION:

 $18.75 \text{cm} \times 11.50 \text{cm} \times 2.54 \text{cm} (7.38" \times 4.53" \times 1.00") \text{ W, D, H}$

PRODUCT WEIGHT: 0.5kg (1.0lbs) approx

SHIPPING

34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

DIMENSION:

SHIPPING WEIGHT: 1.0kg (2.2lbs) approx

POWER

CONSUMPTION:

5V DC, 1.1A

INCLUDED

ACCESSORIES:

Power supply