



KRAMER

VP-2x2

2x2 Computer Graphics Video & Balanced
Stereo Audio Matrix Switcher

| VGA/UXGA - 15-pin HD



The VP-2x2 is a high-performance matrix switcher for computer graphics video signals, with resolutions up to and exceeding UXGA, and balanced stereo audio signals. It can route either or both inputs to either or both outputs simultaneously

FEATURES

High Bandwidth - 400MHz (-3dB) fully loaded

HDTV Compatible

Control - Front panel & RS-232 (K-Router™ Windows®-based Kramer software is included)

Front Panel Control Lockout

Take Button - Executes multiple switches all at once

Audio Breakaway Switching

Desktop Size - Compact size. 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 adapter



KRAMER

TECHNICAL SPECIFICATIONS

INPUTS:	2 VGA/UXGA on 15-pin HD (F) connectors; 2 balanced stereo audio on detachable terminal block connectors
OUTPUTS:	2 VGA/UXGA on 15-pin HD (F) connectors; 2 balanced stereo audio on detachable terminal block connectors
MAX. OUTPUT LEVEL:	Video: 1.7Vpp; audio: 7.2Vpp
BANDWIDTH (-3dB):	Video: 400MHz; audio: 100kHz
DIFF. GAIN:	0.05%
DIFF. PHASE:	0.05Deg
K-FACTOR:	0.05%
S/N RATIO:	Video: 78.3dB; audio: 95dB, unweighted
CROSSTALK:	Video: -43dB; audio: 77dB @ 1kHz
CONTROLS:	Front panel buttons, RS-232
COUPLING:	DC
AUDIO THD + NOISE:	0.049%
AUDIO 2nd HARMONIC:	0.003%
POWER CONSUMPTION:	12V DC, 150mA
INCLUDED ACCESSORIES:	Power supply
OPTIONS:	RK-1 19" rack adapter
PRODUCT DIMENSION:	21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H
PRODUCT WEIGHT:	1.1kg (2.4lbs) approx
SHIPPING DIMENSION:	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H
SHIPPING WEIGHT:	1.5kg (3.4lbs) approx

