



KRAMER

VP-300K

1:3 Computer Graphics Video Distribution Amplifier

| VGA/UXGA - 15-pin HD



The VP-300K is a distribution amplifier for computer graphics signals with resolutions up to and exceeding UXGA. The unit takes one input, provides correct buffering and isolation, and distributes the signal to three identical outputs

FEATURES

High Bandwidth - 400MHz (3dB)

HDTV Compatible

ID Bit Control

Kr-isp® Advanced Sync Processing - Ensures compatibility with a wide range of computers (even if the sync level is too low) by restoring the sync signal waveform. Kr-isp® advanced sync processing can be enabled or disabled

EDID PassThru - Passes EDID signal from display to source via output 1

Selectable Sync Input Impedance - 75 (video), 510 (Graphics/TTL)

DC Coupling

3ft 15-pin HD Cable Included



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|--|
| INPUT: | 1 UXGA on an 15pin HD connector |
| OUTPUTS: | 3 UXGA on 15pin HD connectors |
| MAX. OUTPUT LEVEL: | 2.2Vpp |
| BANDWIDTH (-3dB): | 400MHz |
| DIFF. GAIN: | 0.03% |
| DIFF. PHASE: | 0.03Deg |
| K-FACTOR: | <0.05% |
| S/N RATIO: | 72dB @5MHz |
| CONTROLS: | ID BIT switch; internal analog/TTL switches for setting the sync |
| COUPLING: | DC |
| POWER CONSUMPTION: | 5V DC, 130mA |
| INCLUDED ACCESSORIES: | Power supply (5V/2.6A), mounting bracket |
| OPTIONS: | RK3T 19" rack adapter |
| PRODUCT DIMENSION: | 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H |
| PRODUCT WEIGHT: | 0.2kg (0.4lbs) approx |
| SHIPPING DIMENSION: | 23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H |
| SHIPPING WEIGHT: | 0.7kg (1.5lbs) approx |

