

VP-61xI

6x1 Computer Graphics Video & Balanced Stereo Audio Switcher

| VGA/UXGA - 15-pin HD



The VP-61xl is a high-performance switcher for computer graphics video signals, with resolutions ranging from VGA through UXGA and higher, and balanced stereo audio signals. The VP-61N has all the same features of the VP-61xl but without audio

FEATURES

High Bandwidth - 400MHz (-3dB)

HDTV Compatible

Control - Front panel & RS-232 (K-Router™ Windows®-based Kramer software is included)

Standard 19" Rack Mount Size - 1U



TECHNICAL SPECIFICATIONS

INPUT: 6 analog red, green, blue signals: 0.7Vpp/75, H & V syncs, TTL level on 15-pin HD

(F) connectors; 6 balanced audio stereo signals, +4dBu typical, 24dBu max. on

detachable terminal blocks

OUTPUT: 1 analog red, green, blue signal: 0.7Vpp/75, H & V syncs, TTL level on a 15-pin

HD (F) connector; 1 balanced audio stereo signal, +4dBu typical, 24dBu max. on a

detachable terminal block

BANDWIDTH (-3dB): 400MHz (video); 100kHz (audio)

SWITCH TIME: Less than 5ms

SWITCH CONTROL: Six electronic illuminated touch switches with electronic interlock. RS-232 via an

additional 9-pin D-sub connector on rear panel

COUPLING: Direct

POWER 230V AC, 50/60Hz, (115V AC, USA) 3VA

CONSUMPTION:

INCLUDED Power cord, Windows®-based Kramer control software

ACCESSORIES:

PRODUCT 19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H

DIMENSION:

PRODUCT WEIGHT: 2.8kg (6.3lbs) approx

SHIPPING 55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H

DIMENSION:

SHIPPING WEIGHT: 3.7kg (8.2lbs) approx

