



VS-211HDxI

2x1:2 3G HD-SDI Automatic Standby
Switcher

| 3G HD-SDI - BNC



The VS-211HDxI is a high-performance automatic switcher for 3G HD-SDI video signals. When configured as a standby switcher, it switches to the secondary input when the primary input is lost

FEATURES

Max. Data Rate - 3Gbps

Multi-Standard Operation - SDI (SMPTE 259M and SMPTE 344M), HDSDI (SMPTE 292M) & 3G HDSDI (SMPTE 424M)

HDTV Compatible

Control - Contact closure or automatic switching

Automatic Standby Switching - Switches from the secondary input to the primary input when a primary signal is detected

Primary Input - Selectable

Active Input LED Indicators

Compact DigiTOOLS™ - 3 units can be rack mounted sidebyside in a 1U rack space with the optional RK3T rack adapter



KRAMER

TECHNICAL SPECIFICATIONS

INPUTS:	2 SD/HD/3G HDSDI video on BNC connectors
OUTPUTS:	2 SD/HD/3G HDSDI video on BNC connectors
MAX. OUTPUT LEVEL:	800mVpp/75
DATA RATE:	Up to 2.97Gbps
CONTROLS:	Contact closure remote control, input default selection switch
COUPLING:	AC
POWER CONSUMPTION:	5V DC, 400mA
INCLUDED ACCESSORIES:	Power supply, mounting bracket
OPTIONS:	RK3T 19" rack adapter
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx
SHIPPING DIMENSION:	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H
SHIPPING WEIGHT:	0.6kg (1.3lbs) approx

