

VS-42HDCP

4x2 HDCP Compliant DVI Matrix Switcher

| Ethernet - RJ-45 | HDCP Compliant



The VS-42HDCP is a high-quality, HDCP compliant 4x2 HDMI (on DVI connectors) matrix switcher. It reclocks and equalizes the signals and can route any of the four DVI/HDMI (over DVI-D connector) inputs to any of the two DVI/HDMI outputs simultaneously

FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel)

HDCP Compliant

HDMI Support - Deep Color, x.v.Color™, 3D PassThrough

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances

7.1 Multi-Channel Audio

Front Panel Control Lockout

Communication Support - Support for Kramer Protocol 2000 and Protocol 3000

Flexible Control Options - Front panel, IR (remote included), RS232 (KRouter Plus™ Windows®based software is included), Ethernet (Windows®based Ethernet Configuration Manager & Virtual Serial Port Manager is included), remote extension cable transmitter (optional)

Worldwide Power Supply - 100240V AC



TECHNICAL SPECIFICATIONS

INPUTS: 4 DVI connectors

OUTPUTS: 2 DVI connectors

BANDWIDTH: Up to 6.75Gbps data rate (2.25Gbps per graphic channel)

STANDARDS:

COMPLIANCE WITH Supports DVI and HDCP

MAX RESOLUTION: Up to UXGA; 1080p

POWER SOURCE: 100240V AC; 50/60Hz, 20VA

CONTROLS: Front panel buttons, infrared remote control transmitter, RS232, Ethernet

OPERATING 0° to +40°C (32° to 104°F)

TEMPERATURE:

STORAGE

40° to +70°C (40° to 158°F)

TEMPERATURE:

10% to 90%, RHL noncondensing

HUMIDITY:

PRODUCT DIMENSION: 19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H

Power cord, IR transmitter, rack "ears"

PRODUCT WEIGHT: 1.9kg (4.2lbs) approx

SHIPPING

DIMENSION:

55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H

SHIPPING WEIGHT: 2.7kg (6.0lbs) approx

INCLUDED

ACCESSORIES:

OPTIONS:

External remote IR receiver cable

