



KRAMER

WP-2UC

Active Wall Plate – USB Charger

| DC Power Out



Dual USB Charger, supplied with DECORA® design frame

FEATURES

Two 5V DC USB Power Outlets - Provide up to 20W/4A of total power (shared between the two connectors) for charging mobile devices such as smartphones and tablets

Front Panel Connections - 2 USB-A connectors

Rear Panel Connection - 1 2-pole terminal block for 5V DC



KRAMER

TECHNICAL SPECIFICATIONS

PORTS:	2 USB connectors
POWER CONSUMPTION:	5V DC, 4A
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
PRODUCT DIMENSION:	US: 6.98cm x 0.00cm x 11.43cm (2.75" x 0.00" x 4.50") W, D, H
PRODUCT WEIGHT:	US: 0.1kg (0.2lbs) approx
SHIPPING DIMENSION:	US: 8.00cm x 10.00cm x 5.80cm (3.15" x 3.94" x 2.28") W, D, H
SHIPPING WEIGHT:	US: 0.4kg (0.9lbs) approx