

## Z4KF2XS-DAU

ZyPer4K-XSE Fiber Decoder with Dante and Icron



ZyPer4K-XSE Decoder, accepts IP streaming via 10Gbit/fiber with Dante support. Supports HDMI 2.0 and balanced analog audio output (via 5-pin phoenix). Full USB 2.0 support via Icron chipset on dual USB-B norts. RS232 via 3-pin phoenix connector. Includes ower supply. Audio/Video compatible with any ZyPer4K Encoder. Cables not included

## **FEATURES**

Uncompressed 4K Multiview Video Wall

**HDMI 2.0** 

HDCP 2.3

**AES Encryption** 



## TECHNICAL SPECIFICATIONS

Video HDMI 2.0 with HDCP pass-through

Audio (Digital) Encoded audio formats and linear PCM up to 8 channels

Audio (Analog) Balanced Stereo (Output)

Serial (RS232) 3-pin phoenix

USB Dual USB 2.0 (USB - A connectors)

Ethernet 10 Gb for Video/Audio/Control with 1 Gb Utility

Formats Supports all major VESA resolutions and variations including full HDMI 2.0

support:

VGA: 640x480 (4:3) SXGA: 1280x1024 (5:4) 1080p/i: 1920x1080 (16:9) SVGA: 800x600 (4:3) WXGA: 1366x768 (16:9) QXGA: 2048x1536 (4:3) XGA: 1024x768 (4:3) SXGA+: 1440x1080 (4:3) Ultra HD: 3840x2160 (16:9) HDTV: 1280x720 (16:9) UXGA: 1600x1200 (4:3)

Custom resolutions are supported at pixel clock rates up to 600 MHz

Video Other Color depth: 24 bit, 30 bit, 36 bit, 48 bit

4K: 4096x2160 (17:9)

Video Wall and Multiview Video Wall up to 15x15. Multiview with up to 19 sources

Signal transmission

distance

Multimode Fiber: 300m, Single Mode Fiber: 10km

Copy

Protection/Security

HDCP 2.3, AES-128 Encryption, 802.1X compatible

Power input (locking

connector)

12V DC

Power Approximately 8 watts

Temperature Add Operating temperature: 32 F to 104 F Storage temperature: -4 F to +176 F

New

Humidity Operating/ Storage: 20% to 90% (Non-Condensing)

Accessories Z4KPWRCTR12 ZyPer 12V Power Center for use with up to 8 ZyPer

Encoder/Decoders (all models). 1 RU. Includes rack ears, 8 3-foot locking 12V DC

power cables, AC power cord

Z4KRACKXSE ZyPer4K-XS Rack Mount Kit. Holds up to 8 ZyPer4K-XS

Encoders/Decoders in standard 6RU space. Includes rack assembly and 8 carrier

units

Z4KVESABRK ZyPer4K VESA Bracket is a custom wall/desk/display mount bracket for ZyPer4K. Supports standard VESA parameters for mounting directly to rear of a

display. 100x100, 100x200 and 200x200 VESA hole mounts are supported

Product Dimensions 19.50cm x 0.00cm x 4.82cm (7.68" x 0.00" x 1.90" ) W, D, H

Product Weight 1.0kg (2.2lbs) approx

Shipping Dimensions  $36.60 \text{cm} \times 174.00 \text{cm} \times 8.70 \text{cm} (14.41" \times 68.50" \times 3.43") \text{ W, D, H}$ 

Shipping Weight 1.8kg (3.9lbs) approx