



ZvSync-NA

ZvSync QAM Tuner



ZvSync QAM Tuner is a digital QAM/ATSC tuner/decoder providing video output via composite with analog audio or HDMI with embedded digital audio. Includes IR pigtail, IR remote control and power supply

TECHNICAL SPECIFICATIONS

General	Compliance UL, CE, TuV, CSA, FCC. Low Voltage Directive 2006/95/EC. EN60065:2002+A1:2006. EMC Directive 2004/108/EC. EN 55 013:2001+A1:2003+A2:2006, EN 55 020:2007. EN 61 000-3-2:2006, EN 61 000-3-3:2000 Unit Dimensions (including ports) 13.1 cm x 9.5 cm x 3.1 cm Carton Dimensions (individual) 17 cm x 13.7 cm x 8.5 cm Shipping Weight 18 oz Warranty 1 Year
Tuner	Input Frequency Range 48-862MHz RF Input Level -20 to -82dBm RF Bandwidth 6MHz Modulation ATSC(8VSB) 16QAM, 64QAM, 256QAM
Video	Decoder Format MPEG2 MP@ML/HL Output Format 480i, 480p, 576i, 576p, 720p, 1080i, 1080p60Hz Aspect Ratio 4:3, 16:9, Auto Output Ports HDMI (v1.3C), CVBS
Audio	Decoder Format MPEG-1(layer 1 & 2 & 3), WMA, AC-3 Audio Output Digital Audio over HDMI, RCAx2(L/R)
USB 2.0	Supported Capacity Unlimited Supported Media MP3, WMA, JPEG, BMP, AVI
Power	Supply Voltage (Wall) 100-240VAC 50-60Hz Supply Voltage (ZvSync Unit) 5VDC Maximum Power Consumption 10W Standby Power Consumption <0.8W Nominal Power Consumption 5W
Accessories (Included)	Remote Control AA Batteries (2x) Remote control power

Composite Cable Connects to television when using CVBS output

IR Sensor Connects to IR port, allows tuner to be installed in an unobtrusive location

External Power Supply Connects to AC outlet, provides low voltage DC to tuner unit

Product Dimensions 9.50cm x 0.00cm x 13.10cm (3.74" x 0.00" x 5.16") W, D, H

Product Weight 0.1kg (0.3lbs) approx

Shipping Dimensions 13.70cm x 8.50cm x 17.00cm (5.39" x 3.35" x 6.69") W, D, H

Shipping Weight 0.4kg (0.9lbs) approx

